

**WEST 1/4 CORNER SECTION 12, TOWNSHIP 18 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 491 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 13" X 3-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 11 & 12-18-12.
  
- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 141 DATED MARCH 16, 1883 ORDERED BY OLIVER RIDENOUR TO ESTABLISH THE CENTER CORNER IN SECTION 11-18-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 11-18-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 80.20 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 11-18-12
  
- 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 85 AT THE ORDERED BY EDWIN D. JONES TO PERMANENTLY ESTABLISH THE NORTHEAST CORNER OF SECTION 13-18-12, THE 1/4 CORNER BETWEEN SECTIONS 12 & 13, THE 1/4 CORNER BETWEEN SECTION 13 & 14, AND SUCH OTHER CORNERS OF SAID SECTION 13-18-12 AS MAY BE NECESSARY TO COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 11-18-12 ON THIS **PERMANENT SURVEY** AS HE RAN THE SECTION LINES FROM THE STAKE THAT HE SET AT THE NORTHEAST CORNER OF SECTION 11-18-12 SOUTH TO THE STONE THAT HE SET FOR THE NORTHWEST CORNER OF SECTION 13-18-12. THE SURVEY WAS MADE UPON THE 5<sup>TH</sup>, 6<sup>TH</sup>, 7<sup>TH</sup> AND 8<sup>TH</sup> OF JUNE 1911, AND ENTERED ON THE 19<sup>TH</sup> DAY OF JUNE, 1911. SEE PACKET 167 IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE FOR ANY ADDITIONAL INFORMATION.

WEST QUARTER CORNER SECTION 12-18-12