

NORTH 1/4 CORNER OF SECTION 13, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 491 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 12 & 13-18-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.77 CHAINS WEST TO THE 24" X 14" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14-18-12
 - 2) 39.78 CHAINS EAST TO THE 22" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 12 & 13-18-12 ON THE EAST TOWNSHIP BOUNDARY

- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 85 AT THE ORDERED BY EDWIN D. JONES TO PERMANENTLY ESTABLISH THE NORTHEAST CORNER OF SECTION 13-18-12, THE 1/4 CORNER BETWEEN SECTIONS 12 & 13, THE 1/4 CORNER BETWEEN SECTION 13 & 14, AND SUCH OTHER CORNERS OF SAID SECTION 13-18-12 AS MAY BE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE SET A 18" X 8" X 4" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 13-18-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 13-18-12 AND THE STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 13-18-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. THE SURVEY WAS MADE UPON THE 5, 6, 7 AND 8 OF JUNE, 1911 AND ENTERED ON AUGUST 19, 1911. SEE ALSO PACKET "M 167" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,617' WEST TO THE 24" X 9" X 4-1/2" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 13-18-12
 - 2) 2,617' EAST TO THE 20" X 3" X 6" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 13-18-12 ON THE RANGE LINE

NORTH QUARTER CORNER SECTION 13-18-12