

WEST 1/4 CORNER SECTION 13, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 491 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 13 & 14-18-12.
- 2) H. S. SLEEPER, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 4 ON PAGE 49 OF SURVEY BOOK "A" DATED JANUARY 25, 1860 TO ESTABLISH THE CENTER OF SECTION 14-18-12 AND ALSO TO DIVIDE THE NORTHWEST 1/4 INTO NORTH AND SOUTH HALVES, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE AT THE EAST 1/4 CORNER OF SECTION 14-18-12 ON THIS SURVEY.**
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 75 CHAINS, 75 LINKS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 14-18-12
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 60 RECORDED IN SURVEY BOOK "A" ON PAGE 159 DATED MAY 27, 1868 FOR A SURVEY OF LAND OWNED BY PLUM AND OTHERS, BEING SECTION 14-18-12, TO ESTABLISH THE CENTER CORNER AND DIVIDE THE NORTHWEST 1/4 OF SECTION 14-18-12 EQUALLY BY A LINE RUNNING EAST AND WEST, SAID THAT **HE FOUND THE STONE AT THE EAST 1/4 CORNER OF SECTION 14-18-12 ON THIS SURVEY.**
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 159 RODS, 3 LINKS WEST TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 14-18-12
 - 2) 318 RODS, 19 LINKS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 14-18-12
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 36, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 36 DATED MAY 26, 1870 TO ESTABLISH THE CENTER CORNER OF SECTION 14-18-12 AND TO DIVIDE THE NORTHWEST 1/4, THE NORTHEAST 1/4, AND THE SOUTHEAST 1/4 OF SECTION 14-18-12 BY LINES RUNNING EAST & WEST, SAID THAT **HE FOUND THE STONE AT THE EAST 1/4 CORNER OF SECTION 14-18-12 ON THIS PERMANENT SURVEY.**
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,327' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 14-18-12
 - 2) 2,654' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 14-18-12
 - 3) 1,327' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 14-18-12
 - 4) 2,654' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 14-18-12
- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 85 AT THE ORDERED BY EDWIN D. JONES TO PERMANENTLY ESTABLISH THE NORTHEAST CORNER OF SECTION 13-18-12, THE 1/4 CORNER BETWEEN SECTIONS 12 & 13, THE 1/4 CORNER BETWEEN SECTION 13 & 14, AND SUCH OTHER CORNERS OF SAID SECTION 13-18-12 AS MAY BE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE SET A 16" X 8" X 6" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 13-18-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 13-18-12 AND THE STONE THAT HE SET FOR THE PERMANENT

SOUTHWEST CORNER OF SECTION 13-18-12 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS MADE UPON THE 5TH, 6TH, 7TH AND 8TH OF JUNE, 1911 AND ENTERED ON AUGUST 19, 1911. SEE ALSO PACKET "M 167" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640' SOUTH TO THE 20" X 14" X 12" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 13-18-12
- 2) 2,640' NORTH TO THE 24" X 9" X 4-1/2" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 13-18-12
- 3) 7,920' NORTH TO THE STAKE HE SET FOR THE NORTHEAST CORNER OF SECTION 11-18-12

WEST QUARTER CORNER SECTION 13-18-12