

NORTH 1/4 CORNER SECTION 14, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 495 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 13" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 11 & 14-18-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.88 CHAINS WEST TO THE 21" X 13" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-18-12
 - 2) 39.88 CHAINS EAST TO THE 24" X 14" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14-18-12

- 2) H. S. SLEEPER, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 4 ON PAGE 49 OF SURVEY BOOK "A" DATED JANUARY 25, 1860 TO ESTABLISH THE CENTER OF SECTION 14-18-12 AND ALSO TO DIVIDE THE NORTHWEST 1/4 INTO NORTH AND SOUTH HALVES, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 14-18-12 ON THIS SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 39 CHAINS, 90 LINKS SOUTH TO THE CENTER CORNER OF SECTION 14-18-12

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 60 RECORDED IN SURVEY BOOK "A" ON PAGE 159 DATED MAY 27, 1868 FOR A SURVEY OF LAND OWNED BY PLUM AND OTHERS, BEING SECTION 14-18-12, TO ESTABLISH THE CENTER CORNER AND DIVIDE THE NORTHWEST 1/4 OF SECTION 14 EQUALLY BY A LINE RUNNING EAST AND WEST, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 14-18-12 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 321 RODS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 14-18-12

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 36, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 36 DATED MAY 26, 1870 TO ESTABLISH THE CENTER CORNER OF SECTION 14-18-12 AND TO DIVIDE THE NORTHWEST 1/4, THE NORTHEAST 1/4, AND THE SOUTHEAST 1/4 OF SECTION 14 BY LINES RUNNING EAST & WEST, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 14-18-12 ON THIS **PERMANENT SURVEY**. [**NOTE:** THE NUMBERS ON HIS SURVEY NOTES AND HIS SURVEY DRAWING DO NOT MATCH BETWEEN THE NORTH 1/4 CORNER AND THE SOUTH 1/4 CORNER OF SECTION 14-18-12 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,321' SOUTH TO THE STONE HE FOUND AT THE WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 14-18-12
 - 2) 2,647' SOUTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 14-18-12
 - 3) 4,285' SOUTH TO WHERE THE A. T. & S. F. RAILROAD COURSES N. 47°30' E.
 - 4) 5,295' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 14-18-11HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,321-1/2' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 14-18-11
 - 2) 2,643' SOUTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 14-18-11
 - 3) 3,981' SOUTH TO THE LOCATION FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 14-18-11—FALLS IN A CREEK

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 5,319' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 14-18-11

- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 141 DATED MARCH 16, 1883 ORDERED BY OLIVER RIDENOUR TO ESTABLISH THE CENTER CORNER IN SECTION 11-18-12, SAID THAT **HE FOUND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 11-18-12 ON THIS PERMANENT SURVEY.**
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 80.34 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 11-18-12

NORTH QUARTER CORNER 14-18-12