

NORTH 1/4 CORNER SECTION 15, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 498 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 15-18-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.05 CHAINS WEST TO THE 18" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-18-12
 - 2) 40.05 CHAINS EAST TO THE 21" X 13" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-18-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 68 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 125 DATED MARCH 24, 1875 TO ESTABLISH THE CENTER CORNER AND THE CORNERS TO THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 15-18-12, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTIONS 15-18-12 ON THIS **PERMANENT SURVEY**. HE NOTED THAT THE PARTIES FOR WHOM THIS SURVEY WAS MADE AGREED TO REPLACE ALL THE POSTS THAT HE SET ON THIS SURVEY WITH STONE CORNERS AS STONE WAS NOT AVAILABLE AT THE TIME OF THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,658' SOUTH TO THE POST HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 15-18-12
 - 2) 5,306' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 15-18-12

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 161, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 161 DATED MARCH 30 & 31, 1887 ORDERED BY WILLIAM ELSDON TO SURVEY THE WEST 1/2 AND THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 10-18-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 10-18-12 ON THIS **PERMANENT SURVEY**.

NORTH 1/4 CORNER SECTION 15-18-12