

**NORTH 1/4 CORNER SECTION 16, TOWNSHIP 18 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 502 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 16-18-12.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.93 CHAINS WEST TO THE 14" X 9" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-18-12
  - 2) 39.94 CHAINS EAST TO THE 18" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-18-12
  
- 2) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 65 AT THE REQUEST OF OL RIDENOUR REQUIRING HIM TO SURVEY A 45-7/11 ACRE TRACT ALONG THE NORTH SIDE OF THE NORTHEAST 1/4 OF SECTION 10-18-12, SAID THAT **HE FOUND THE NORTH 1/4 STONE** OF SECTION 16-18-10 ON THIS **PERMANENT SURVEY**. HE USED HIS STONE TO VERIFY THE STAKE THAT HE SET FOR THE TRUE POSITION OF THE NORTHWEST CORNER OF SECTION 16-18-12. THE SURVEY WAS MADE ON MAY 31 AND JUNE 3, 1910 AND ENTERED ON JUNE 9, 1910.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,650' WEST TO THE STAKE HE SET FOR THE TRUE POSITION FOR THE NORTHWEST CORNER OF SECTION 16-18-12
  - 2) 2,650' EAST TO THE STAKE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 16-18-12
  
- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F09002 IN THE SURVEY FILE FOR TOWNSHIP 18-12 TO DETERMINE THE CORNERS TO A 10 ACRE TRACT OF GROUND DESCRIBED AS THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 9-18-12 FOR RALPH SHELLHAMER DATED NOVEMBER 21, 1973, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 9-18-12. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 25' NORTH TO A FENCE CORNER POST
  - 2) 660' NORTH TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE 10 ACRE TRACT
  - 3) 660' EAST TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE 10 ACRE TRACT
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 3, 2003, FOR PROJECT NUMBER 03371-02, SURVEY F09003 IN THE SURVEY FILE FOR TOWNSHIP 18-12 FOR THE SURVEY OF A 40.0 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 9-18-12, SAID THAT **HE FOUND A 1/2" REBAR** AT THE SOUTH 1/4 CORNER OF SECTION 9-18-12 FROM A SURVEY BY LESLIE M. GOULD, L.S. 142, ON FILE IN THE COUNTY ENGINEER'S OFFICE.
  - 1) 30.8' NE TO A 40 D NAIL & WASHER IN A POWER POLE
  - 2) 27.5' SOUTH TO A CONCRETE NAIL & FIBERGLASS TAB IN A CORNER FENCE POST
  - 3) 35.2' SW TO A CONCRETE NAIL & FIBERGLASS TAB IN A FENCE GATE POST
  - 4) IN THE CENTERLINE OF TRAVELED WAY OF COUNTY ROAD 230 EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,320.00' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 40.0 ACRE TRACT

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,648.52' WEST TO THE STONE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 9-18-12
- 3) 1,320.00' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 40.0 ACRE TRACT
- 4) 5,293.09' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 9-18-12

NORTH 1/4 CORNER SECTION 16-18-12