

**WEST 1/4 CORNER SECTION 16, TOWNSHIP 18 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 501 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 20" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 17-18-12.
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 40, A SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 40 DATED JUNE 13 & 20, 1884 AT THE REQUEST OF JONES & PARKER TO LOCATE THE CENTER, WEST 1/4 CORNER, AND THE NORTHEAST AND NORTHWEST CORNERS OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8-18-12, APPARENTLY DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 16-18-12 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-18-12 SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 20-18-12, AND HE DOES NOT MENTION THE WEST 1/4 CORNER OF SECTION 16-18-12.
- 3) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 65 AT THE REQUEST OF OL RIDENOUR REQUIRING HIM TO SURVEY A 45-7/11 ACRE TRACT ALONG THE NORTH SIDE OF THE NORTHEAST 1/4 OF SECTION 10-18-12, SAID THAT **HE FOUND THE WEST 1/4 STONE** OF SECTION 16-18-12 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS MADE MAY 31 AND JUNE 3, 1910 AND ENTERED ON JUNE 9, 1910.

WEST QUARTER CORNER SECTION 16-18-12