

NORTH 1/4 CORNER SECTION 20, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 506 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 27" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-18-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS WEST TO THE 22" X 20" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-18-12
 - 2) 39.95 CHAINS EAST TO THE 18" X 14" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21

- 2) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 35 SAYS THAT **THEY SET AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 20-18-12 AT 2,653.7 FEET EAST OF THE NORTHWEST CORNER OF SECTION 20-18-12 AND IN LINE WITH FENCES TO THE NORTH AND SOUTH.
 - 1) 21' SOUTH TO A WITNESS PIN

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-12 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 17-18-12" AND "NW CORNER NE1/4 SECTION 20-18-12". **MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 21' SOUTH TO A WITNESS [REA]

NORTH QUARTER CORNER SECTION 20-18-12