

WEST 1/4 CORNER SECTION 20, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 505 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 27" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 20-18-12.
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 29, AN **AGREEMENT SURVEY** REQUESTED BY J. M. KNOX TO LOCATE THE SOUTHWEST CORNER, SOUTH 1/4 CORNER, AND SOUTHEAST CORNER OF SECTION 19-18-12 RECORDED IN SURVEY BOOK "E" ON PAGE 29 DATED MAY 8, 1884, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 19-18-12. HE USED THIS STONE TO SET THE SOUTHEAST CORNER OF SECTION 19-18-12 ON THIS **AGREEMENT SURVEY**.
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A SURVEY FILED MAY 17, 1884 AND RECORDED IN VOLUME 41 ON PAGE 17 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 29, 1887, SURVEY F19002 IN THE SURVEY FILE FOR TOWNSHIP 18-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 20-18-12 ON THIS SURVEY.
- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 434 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 638 TO 640 PETITIONED BY HENRY GOOD AND OTHERS FOR A ROAD IN TOWNSHIP 18-12 [PACKET 670 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 20, 1897, WAS ESTABLISHED AS A **50 AND 80 FOOT WIDE ROAD** ON OCTOBER 9, 1897 AS NOTED BY J. A. MILLES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY M. O. STARR, COUNTY CLERK, AND RECORDED ON DECEMBER 26, 1899 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 20-18-12 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES **AT 50 FEET WIDE** TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-18-12 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH AT **50 FEET WIDE** FOR 29 CHAINS SOUTH TO A SANDSTONE, THEN ANGLE TO THE RIGHT OF 41° 07' FOR 3.50 CHAINS **AT 80 FEET WIDE** TO A SANDSTONE, THEN ANGLE TO THE LEFT OF 52° FOR 7.36 CHAINS **AT 50 FEET WIDE** TO A LIMESTONE MARKED "R/1M", THEN IN THE SAME DIRECTION AT **50 FEET WIDE** FOR 1.37 CHAINS TO THE STONE IN THE EAST-WEST ROAD AT THE TERMINUS OF THIS ROAD SURVEY
- 5) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 35 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 20-18-12 AT 2,663.7 FEET NORTH OF THE SOUTHWEST CORNER OF SECTION 29-18-12, IN LINE WITH HEDGES TO THE EAST AND WEST, AND IN THE CENTER OF THE ROAD.
 - 1) 22' EAST TO A WITNESS PIN 5" NORTH OF A LARGE HEDGE POST
- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-12 SHOWS A **REA PIN** AT THE "SE CORNER NE 1/4 SECTION 19-18-12" AND "SW CORNER NW1/4 SECTION 20-18-12". **MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 22' EAST TO A WITNESS [REA]

WEST QUARTER CORNER SECTION 20-18-12