

WEST 1/4 CORNER SECTION 22, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 497 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 21 & 22-18-12.

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 53, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 234 DATED JULY 5, 1902 ORDERED BY JOHN BLAHUT, CASPER TROLL, AND THE ESTATE OF WALTER S. WILSEY TO SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 27-18-12, SAID THAT HE DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 22-18-12 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE THAT FOUND AT THE SOUTHEAST CORNER OF SECTION 33-18-12 ON THE TOWNSHIP LINE NORTH TO THE 1/8TH STONE THAT HE FOUND ON THE EAST SIDE OF THE SOUTHEAST 1/4 OF SECTION 16-18-12, AND DOES NOT MENTION THE WEST 1/4 CORNER OF SECTION 22-18-12 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 80, AND ADDITIONAL INFORMATION IS IN PACKET "M 44" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

WEST QUARTER CORNER SECTION 22-18-12