

**NORTH 1/4 CORNER OF SECTION 23, TOWNSHIP 18 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 494 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-18-12 ON JANUARY 27, 1857. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.75 CHAINS WEST TO THE 22" X 11" X 13" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-18-12
  - 2) 39.75 CHAINS EAST TO THE 21" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-18-12
  
- 2) H. S. SLEEPER, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 4 ON PAGE 49 OF SURVEY BOOK "A" DATED JANUARY 25, 1860 TO ESTABLISH THE CENTER OF SECTION 14-18-12 AND ALSO TO DIVIDE THE NORTHWEST 1/4 INTO NORTH AND SOUTH HALVES, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 14-18-12 ON THIS SURVEY.
  
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 60 RECORDED IN SURVEY BOOK "A" ON PAGE 159 DATED MAY 27, 1868 FOR A SURVEY OF LAND OWNED BY PLUM AND OTHERS, BEING SECTION 14-18-12, TO ESTABLISH THE CENTER CORNER AND DIVIDE THE NORTHWEST 1/4 OF SECTION 14 EQUALLY BY A LINE RUNNING EAST AND WEST, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 14-18-12 ON THIS SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 321 RODS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 14-18-12
  
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 36, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 36 DATED MAY 26, 1870 TO ESTABLISH THE CENTER CORNER OF SECTION 14-18-12 AND TO DIVIDE THE NORTHWEST 1/4, THE NORTHEAST 1/4, AND THE SOUTHEAST 1/4 OF SECTION 14 BY LINES RUNNING EAST & WEST, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 14-18-12 ON THIS **PERMANENT SURVEY**. **[NOTE:** THE NUMBERS ON HIS SURVEY NOTES AND HIS SURVEY DRAWING DO NOT MATCH BETWEEN THE NORTH 1/4 CORNER AND THE SOUTH 1/4 CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR] HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 1,010' NORTH TO THE A. T. & S. F. RAILROAD COURSES N. 47°30' E.
  - 2) 2,648' NORTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 14-18-12
  - 3) 3,974' NORTH TO THE STONE HE FOUND AT THE WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 14-18-12
  - 4) 5,295' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 14-18-12HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,010' NORTH TO THE A. T. & S. F. RAILROAD COURSES N. 47°30' E.
  - 2) 1,338' NORTH TO THE LOCATION FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 14-18-12—FALLS IN A CREEK
  - 3) 2,676' NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 14-18-12
  - 4) 3,997-1/2' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 14-18-12
  - 5) 5,319' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 14-18-12

CONTINUED ON PAGE 2

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 208 [PACKET 75 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY GEORGE PLUMB AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 18-12 THAT HE SURVEYED ON JANUARY 22, 1873, AND WAS ORDERED ESTABLISHED AS A 60 FOOT WIDE ROAD BY THE COUNTY COMMISSIONERS HELD APRIL 7, 1873 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SHOWS ON HIS SURVEY DRAWING AND STATES IN HIS NOTES THAT THE CENTER OF THIS ROAD PASSES THROUGH THE NORTH 1/4 CORNER OF SECTION 23-18-12 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR ONE AND ONE-HALF MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 24-18-12 ON THE RANGE LINE TO BEGIN THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 107-1/4 RODS TO A POST HE SET AT 75 FEET FROM THE CENTER OF THE TRACK OF THE ATCHISON TOPEKA AND SANTA FE RAILROAD ON THE WEST SIDE OF THE SAME, THEN TURNS SOUTHWESTERLY PARALLEL AND 25 FEET DISTANCE FROM SAID RAILROAD FOR 3 MILES AND 260 RODS TO INTERSECT THE TOWNSHIP LINE BETWEEN SECTIONS 31 & 6, TOWNSHIPS 18 & 19, RANGE 12 TO END THIS ROAD SURVEY
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY NUMBER 87 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 9 DATED FEBRUARY 11, 1873 TO ESTABLISH THE CORNERS OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 23-18-12, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-18-12 ON THIS **PERMANENT SURVEY**. [NOTE: THE WORDING IN THE DESCRIPTION HAS TOWNSHIP 18, RANGE 11, BUT THERE IS A REFERENCE IN THE FIELD NOTES TO CROSSING BADGER CREEK, MAKING THIS SURVEY IN TOWNSHIP 18, RANGE 12, WHICH CORRESPONDS TO THE HEADING AT THE TOP OF THE LEFT PAGE. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]  
HIS SURVEY NOTES/DRAWING INDICATES THE FOLLOWING INFORMATION:
- 1) 1,329' SOUTH TO THE POST HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 23-18-12 "THE GROUND BEING FROZEN TOO HARD TO SET A STONE"
  - 2) 2,658' SOUTH TO THE POST HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 23-18-12 "THE GROUND BEING FROZEN TOO HARD TO SET A STONE"
  - 3) 3,934' SOUTH TO THE POST HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 23-18-12 "THE GROUND BEING FROZEN TOO HARD TO SET A STONE"
  - 4) 5,310' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 23-18-12

NORTH QUARTER CORNER SECTION 23-18-12