

NORTH 1/4 CORNER OF SECTION 24, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 491 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 13 & 24-18-12 .

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.62 CHAINS WEST TO A 21" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-18-12
- 2) 39.62 CHAINS EAST TO A 20" X 14" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13 & 24-18-12 ON THE EAST TOWNSHIP BOUNDARY

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 90 RECORDED IN SURVEY BOOK "A" ON PAGE 184 DATED FEBRUARY 15, 1869 FOR A SURVEY OF LAND OWNED BY WELLS, BEING IN SECTION 24-18-12, TO SURVEY THE SOUTH 1/2 OF THE NORTHWEST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 24-18-12, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 24-18-12 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 319 RODS, 5 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 24-18-12

- 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 85 AT THE ORDERED BY EDWIN D. JONES TO PERMANENTLY ESTABLISH THE NORTHEAST CORNER OF SECTION 13-18-12, THE 1/4 CORNER BETWEEN SECTIONS 12 & 13, THE 1/4 CORNER BETWEEN SECTION 13 & 14, AND SUCH OTHER CORNERS OF SAID SECTION 13 AS MAY BE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE SET A 15" X 6" X 6" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE** FOR THE SOUTH 1/4 CORNER OF SECTION 13-18-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER AND THE STONE THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 13-18-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. THE SURVEY WAS MADE UPON THE 5TH, 6TH, 7TH AND 8TH OF JUNE, 1911 AND ENTERED ON AUGUST 19, 1911. SEE ALSO PACKET "M 167" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION

- 1) 2,615' WEST TO THE 20" X 14" X 12" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 13-18-12
- 2) 2,615' EAST TO THE 18" X 8" X 6" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 13-18-12 ON THE RANGE LINE

- 4) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F24001 IN THE SURVEY FILE FOR TOWNSHIP 18-12, A SURVEY TO ESTABLISH CONTROL POINTS ON THE NORTH LINE OF THE NORTHWEST 1/4 OF SECTION 24-18-12 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR PROJECT 15-29 DATED FEBRUARY 1, 2016, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER AND **HE FOUND THE EXISTING 15" X 6" X 6" LIMESTONE FIRM IN THE GROUND** AT THE NORTH 1/4 CORNER OF SECTION 24-18-12 THAT WAS SET BY MATTHEW BROWN IN 1911 AS RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 85. THIS STONE IS AT LYON COUNTY PROJECT 15-29 STATION 26+36.52.

- 1) 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP SET ON THE NORTH SIDE CENTER OF THE STONE

HIS TIES ARE CONTINUED ON PAGE 2

- 2) 1/2" X 24" IRON PIN WITH HIS "PS 752" CAP SET ON THE SOUTH SIDE CENTER OF THE STONE
- 3) 42.5' NE TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF A BRACE POST
- 4) 27.3' SOUTH TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE
- 5) 48.2' SW TO THE NEAR FACE OF A 4" PIPE GATE POST
- 6) 32.4' NNW TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF A BRACE POST
- 7) 2.5' NORTH TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD 220 EAST-WEST
- 8) 3' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,109.02' WEST TO THE 5/8" X 6" IRON PIN WITH A LYON COUNTY CAP HE SET AT PROJECT 15-29 P.O.T. STATION 15+27.50
- 2) 1,709.02' WEST TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET AT PROJECT 15-29 P.O.T. STATION 9+27.50
- 3) 2,636.52' WEST TO THE 1/2" IRON PIN WITH HIS "PS 752" CAP BENT OVER THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-18-12 AT PROJECT 15-29 STATION 0+00.00

NORTH QUARTER CORNER SECTION 24-18-12