

WEST 1/4 CORNER SECTION 24, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 490 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 17" X 1-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 24-18-12.

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 90 RECORDED IN SURVEY BOOK "A" ON PAGE 184 DATED FEBRUARY 15, 1869 FOR A SURVEY OF LAND OWNED BY WELLS, BEING IN SECTION 24-18-12, TO SURVEY THE SOUTH 1/2 OF THE NORTHWEST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 24-18-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 24-18-12 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 159 RODS, 15 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-18-12
 - 2) 159 RODS, 3-1/2 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 24-18-12

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY NUMBER 87 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 9 DATED FEBRUARY 11, 1873 TO ESTABLISH THE CORNERS OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 23-18-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 23-18-12 ON THIS **PERMANENT SURVEY**. [**NOTE:** THE WORDING IN THE DESCRIPTION HAS TOWNSHIP 18, RANGE 11, BUT THERE IS A REFERENCE IN THE FIELD NOTES TO CROSSING BADGER CREEK, MAKING THIS SURVEY IN TOWNSHIP 18, RANGE 12, WHICH CORRESPONDS TO THE HEADING AT THE TOP OF THE LEFT PAGE – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
HIS SURVEY NOTES/DRAWING INDICATES THE FOLLOWING INFORMATION:
 - 1) 1,324-1/2' NORTH TO THE POST HE SET FOR A PERMANENT EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 23-18-12 "THE GROUND BEING TOO FROZEN TO SET A STONE"
 - 2) 2,649' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 23-18-12
 - 3) 1,322' SOUTH TO A STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER ON OF THE SE1/4 OF SECTION 23-18-12
 - 4) 2,644' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 23-18-12
 - 5) 2,637-1/2' WEST TO THE POST HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 23-18-12 "THE GROUND BEING TOO FROZEN TO SET A STONE"
 - 6) 5,269' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 23-18-12

- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-12 SHOWS A **STONE** AT THE "SW CORNER NW1/4 SECTION 24-18-12".
 - 1) 39.2' NE TO AN IRON PIN IN A HEDGE
 - 2) 35.3' SE TO AN IRON PIN IN A HEDGE

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-12 SHOWS A **STONE & PIN** AT THE "W1/4 CORNER SECTION 24-18-12".
 - 1) 28' EAST TO THE BASE OF A STUMP
 - 2) 27.6' WEST TO THE BASE OF A LARGE POST
 - 3) 35.3' SE TO A REBAR

CONTINUED ON PAGE 2

- 6) KRETSINGER REFERENCE TIE BOOK NUMBER 13 ON PAGE 30 AT THE TOP OF THE PAGE SHOWS A **LIMESTONE** AT THE "W1/4 CORNER SECTION 24-18-12".
- 1) 39.2' NE TO A 1/2" SQUARE IRON PIN
 - 2) 28.2' EAST TO THE BASE OF A 18" X 4' HEDGE STUMP
 - 3) 35.3' SE TO A 1/2" SQUARE IRON PIN

WEST QUARTER CORNER SECTION 24-18-12