

WEST 1/4 CORNER SECTION 25, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 490 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 14" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 26-18-12.

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 113 RECORDED IN SURVEY BOOK "A" ON PAGES 203 & 204 DATED MAY 11, 1869 FOR A SURVEY OF SECTIONS 25 & 26-18-12, TO SURVEY THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26, AND THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 26, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 26-18-12 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 159 RODS, 14 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-18-12
 - 2) 159 RODS, 10 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-18-12
 - 3) 80 RODS WEST TO THE STONE HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 26-18-12
 - 4) 80 RODS EAST TO THE STONE HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 25-18-12

- 3) FINNEY & TURNIPSEED PLANS FOR BRIDGE NUMBER FAS 677, **SET A 1/2" REBAR** AT THE **"APPARENT CORNER"**. **NOTE: VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE ACCEPTING THIS APPARENT CORNER AS THIS 1/2" REBAR WAS PROBABLY "HEELED-IN" FOR THIS BRIDGE SURVEY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) P.O.T. STATION 158 + 28.40
 - 2) 44.30' SE TO A SPIKE IN THE CROTCH OF A 15" TREE
 - 3) 26.40' WEST TO A SPIKE IN THE TOP OF A FENCE POST
 - 4) 30.80' SW TO A SPIKE IN THE TOP OF A GATE POST

WEST QUARTER CORNER SECTION 25-18-12