

**WEST 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 25, TOWNSHIP 18 SOUTH,  
RANGE 12 EAST**

- 1) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN SURVEY NUMBER 2 RECORDED IN SURVEY BOOK "A" ON PAGE 48 AND DATED JANUARY 1860, SAID THAT **HE SET A STONE** FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 25-18-12 ON THIS SURVEY.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 113 RECORDED IN SURVEY BOOK "A" ON PAGES 203 & 204 DATED MAY 11, 1869 FOR A SURVEY OF SECTIONS 25 & 26-18-12, TO SURVEY THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 26, AND THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SAID SECTION 26, SAID THAT **HE SET A STONE** FOR THE EAST 1/2/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 26-18-12 EQUIDISTANT BETWEEN THE STONES THAT HE FOUND AT THE EAST 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 26-18-12 ON THIS SURVEY.
- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F26001 IN THE SURVEY FILE FOR TOWNSHIP 18-12 FOR THE SURVEY OF A 3.03 ACRE TRACT IN THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26-18-12 DATED JANUARY 24, 1974, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26-18-12. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 338' WEST TO THE IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE 3.03 ACRE TRACT
  - 2) 390' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE 3.03 ACRE TRACT
- 4) FINNEY & TURNIPSEED PLANS FOR BRIDGE NUMBER FAS 677, SHOWS THAT THEY SET A **1/2" REBAR** AT THE **"APPARENT CORNER"**. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS REBAR MAY HAVE BEEN "HEELED-IN" FOR THE BRIDGE SURVEY! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) P.O.T. STATION 145 + 00.00
  - 2) 28.60' WEST TO A SPIKE IN THE TOP OF A CORNER FENCE POST
  - 3) 68.35' SW TO A SPIKE IN A POWER POLE
  - 4) 100.85' NW TO A SPIKE IN A POWER POLE

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 25-18-12