

WEST 1/4 CORNER SECTION 26, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 493 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 27-18-12.

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 113 RECORDED IN SURVEY BOOK "A" ON PAGES 203 & 204 DATED MAY 11, 1869 FOR A SURVEY OF SECTIONS 25 & 26-18-12, TO SURVEY THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26, AND THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 26, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 26-18-12 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 240 RODS EAST TO THE STONE HE SET FOR THE SOUTH 1/2 OF THE NE1/4 OF SECTION 26-18-12
 - 2) 320 RODS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 26-18-12

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 53, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 234 DATED JULY 5, 1902 ORDERED BY JOHN BLAHUT, CASPER TROLL, AND THE ESTATE OF WALTER S. WILSEY TO SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 27-18-12, SAID THAT **HE SET A 22" X 15" X 2-1/2" STONE ON LINE WITH A FENCE** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 27-18-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-18-12 AND THE STAKE THAT HE DROVE FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 27-18-12 ON THIS **PERMANENT SURVEY**. HE SAID THAT HE TOOK THE AFFIDAVIT OF W. E. LOOMIS IN REGARDS TO THE POSITION OF THE ORIGINAL STONE. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 80, AND ADDITIONAL INFORMATION IS IN PACKET "M 44" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.06-1/2 CHAINS NORTH TO THE 24" X 12" 2" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER ON THE S1/2 OF THE NE1/4 OF SEC. 27-18-12
 - 2) 40.13 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-18-12
 - 3) 40.13 CHAINS SOUTH TO THE SQUARE STAKE HE DROVE FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 27-18-12

WEST QUARTER CORNER SECTION 26-18-12