

**WEST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 26, TOWNSHIP 18 SOUTH,
RANGE 12 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 53, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 234 DATED JULY 5, 1902 ORDERED BY JOHN BLAHUT, CASPER TROLL, AND THE ESTATE OF WALTER S. WILSEY TO SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 27-18-12, SAID THAT **HE SET A 24" X 12" X 2" STONE ON LINE WITH A FENCE** FOR THE PERMANENT NORTHEAST CORNER OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 27-18-12 ON TRANSIT LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-18-12 AND THE STONE THAT HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 27-18-12 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 80, AND ADDITIONAL INFORMATION IS IN PACKET "M 44" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.06-1/2 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-18-12
 - 2) 20.06-1/2 CHAINS SOUTH TO THE 22" X 15" X 2-1/2" STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 27-18-12, AND HE TOOK THE AFFIDAVIT OF W. E. LOOMIS IN REGARDS TO THE POSITION OF THE ORIGINAL STONE
 - 3) 60.19-1/2 CHAINS SOUTH TO THE SQUARE STAKE HE DROVE FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 27-18-12

WEST SIXTEENTH CORNER NORTHWEST QUARTER 26-18-12