

WEST 1/4 CORNER SECTION 29, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 504 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 15" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 30-18-12.

- 2) G. M. WALKER, DEPUTY SURVEYOR, IN SURVEY NUMBER 34 RECORDED IN SURVEY BOOK "A" ON PAGES 68 & 69 DATED MAY 15, 1861 TO ESTABLISH THE WEST 1/4 POST OF SECTION 29-18-12, "THE GOVERNMENT CORNER BEING LOST AND NO EVIDENCE TO BE HAD OF ITS ORIGINAL POSITION", SAID THAT **HE SET A STONE MARKED "1/4" FOR THE WEST 1/4 POST** OF SECTION 29-18-12 ON LINE AND HALFWAY BETWEEN THE STONE POST THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-18-12 AND THE STONE POST THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-18-12 ON THIS SURVEY. HE NOTED: "STONE 1/4 POST SET ABOUT 12 FEET NORTH OF MIDDLE OF CHANNEL OF PLUMB CREEK. IT WOULD BE COVERED IN HIGH STATE OF WATER". HE MARKED A WITNESS TREE; A BOX ELDER 15" IN DIAMETER, AT 1.5 LINKS WEST.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.30 CHAINS NORTH TO THE STONE POST HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-18-12
 - 2) 40.30 CHAINS SOUTH TO THE STONE POST HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-18-12

- 3) G. M. WALKER, DEPUTY SURVEYOR, IN SURVEY NUMBER 35 RECORDED IN SURVEY BOOK "A" ON PAGES 69 & 70 DATED MAY 15, 1861 TO ESTABLISH THE CORNERS OF DAVID GILMORES LAND, BEING THE WEST 1/2 AND THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12, SAID THAT **HE FOUND THE STONE WEST 1/4 POST** OF SECTION 29-18-12 ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.00-1/2 CHAINS EAST TO THE STAKE HE SET FOR THE N1/4/4 POST OF THE SW1/4 OF SECTION 29-18-12
 - 2) 40.01 CHAINS EAST TO THE STONE HE SET FOR THE CENTER POST OF SECTION 29-18-12
 - 3) 80.04 CHAINS EAST TO THE FOUND STONE EAST 1/4 POST OF SECTION 29-18-12

- 4) G. M. WALKER, DEPUTY SURVEYOR, IN SURVEY NUMBER 36 RECORDED IN SURVEY BOOK "A" ON PAGES 70 & 71 DATED MAY 16, 1861 TO ESTABLISH THE CENTER POST OF SECTION 30-18-12, SAID THAT **HE FOUND THE STONE EAST 1/4 POST** OF SECTION 30-18-12 ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 40.32 CHAINS WEST TO THE STONE HE SET FOR THE CENTER POST OF SECTION 30-18-12
 - 2) 76.00 CHAINS WEST TO THE FOUND STONE WEST 1/4 POST OF SEC. 30-18-12

- 5) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 49, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 48 DATED MAY 31 AND JUNE 4, 1870 TO ESTABLISH THE 1/4/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 30-18-12 AND THE 1/4/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 30-18-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 30-18-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,326-1/4' NORTH TO THE POST HE SET FOR THE EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 30-18-12
 - 2) 2,652-1/2' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-18-12

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 1,285-1/5' SOUTH TO THE POST HE SET FOR THE EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 30-18-12
- 4) 2,571' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 30-18-12 IN THE CENTER OR MIDDLE OF PLUMB CREEK

- 6) REA BOOK 30 ON PAGE 35 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE EAST 1/4 CORNER OF SECTION 30-18-12 AT 2,661 FEET EAST OF THE CENTER CORNER OF SECTION 30-18-12.
 - 1) 18' NORTH TO A WITNESS PIN
 - 2) 10.4' SE TO THE CORNER OF THE CONCRETE CROSSING OF PLUMB CREEK
 - 3) 11' NE TO THE OTHER CORNER OF THE CROSSING

- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-12 SHOWS A **REA PIN** AT THE "SW CORNER NW1/4 SECTION 29-18-12".
 - 1) 18' NORTH TO A WITNESS [REA]

- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 63 TO LOCATE AND PERMANENTLY ESTABLISH THE CENTER CORNER OF SECTION 29-18-12, THE NORTHWEST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12, AND THE NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12 PETITIONED BY PAUL G. WALKER, RECORD OWNER OF THE SOUTHEAST 1/4 AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12 THAT BEGAN ON MAY 10, 1988 AND CONTINUED UNTIL COMPLETED ON JUNE 29, 1988, SAID THAT HE DETERMINED THAT THE WEST 1/4 CORNER OF SECTION 29-18-12 WAS **LOST**. **HE SET A 1/4" PK NAIL & WASHER IN THE CONCRETE SURFACE OF THE LOW WATER CROSSING** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-18-12 ON LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER OF SECTION 29-18-12 AND THE SOUTHWEST CORNER OF SECTION 29-18-12 ON THIS **PERMANENT SURVEY**.
 - 1) 16.3' NE TO THE NORTHEAST CORNER OF THE CONCRETE CROSSING
 - 2) 17.3' SW TO THE SOUTHEAST CORNER OF THE CONCRETE CROSSING
 - 3) 46.95' NW TO THE NORTHWEST CORNER OF THE CONCRETE CROSSING
 - 4) 13.45' EAST TO THE EAST EDGE OF THE WEARING SURFACE OF THE CONCRETE CROSSING
 - 5) 11.05' SOUTH TO THE SOUTH EDGE OF THE LOW WATER CROSSING
 - 6) 9.05' NORTH TO THE NORTH EDGE OF THE LOW WATER CROSSING
 - 7) 50.00' WNW TO A 5/8" REBAR DRIVEN INTO THE NORTH EDGE OF THE ROAD
 - 8) 50.00' ENE TO A 5/8" REBAR DRIVEN INTO THE NORTH EDGE OF THE ROAD
 - 9) 40.8' SE TO A PK NAIL & WASHER IN A POWER POLE
 - 10) SURVEY COORDINATES: N: 12736.098 E: 14495.196

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,659.98' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-18-12
 - 2) 1,329.99' SOUTH TO THE LOCATION FOR THE NORTHWEST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 29-18-12—FALLS IN A CREEK, SO HE SET 5/8" REBARS WITH LYON COUNTY CAPS AS WITNESSES AT 10.0' NORTH AND 70.0' EAST
 - 3) 2,659.98' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-18-12
 - 4) 2,645.53' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-18-12

- 9) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 9, 1996, **FOUND THE 1/4" PK NAIL & WASHER IN THE CONCRETE SURFACE OF THE LOW WATER CROSSING** AT THE WEST 1/4 CORNER OF SECTION 29-18-12 FROM EXISTING TIES OF RECORD IN THE

COUNTY ENGINEER'S OFFICE FROM THE PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 63 FILED JUNE 29, 1988 BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR.

- 1) 30.1' NE TO THE NORTHEAST CORNER OF THE LOW WATER CROSSING
 - 2) 30.5' SE TO THE SOUTHEAST CORNER OF THE LOW WATER CROSSING
 - 3) 45.3' NW TO THE NORTHWEST CORNER OF THE LOW WATER CROSSING
 - 4) 46.2' SE TO THE SOUTHWEST CORNER OF THE LOW WATER CROSSING
 - 5) 11.05' SOUTH TO THE SOUTH EDGE OF THE LOW WATER CROSSING
 - 6) 9.05' NORTH TO THE NORTH EDGE OF THE LOW WATER CROSSING
 - 7) 40.8' SE TO A PK NAIL & WASHER IN A POWER POLE
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 20, 2011 FOR PROJECT NUMBER 11174-02, SURVEY F30003 IN THE SURVEY FILE FOR TOWNSHIP 18-12 FOR A 10.00 ACRE TRACT IN THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 30 FOR EK REALTY, SAID THAT **HE FOUND THE PK NAIL AND WASHER IN THE CONCRETE SURFACE OF A LOW WATER CROSSING** AT THE EAST 1/4 CORNER OF SECTION 30-18-12 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT HE HAD SET THIS PK NAIL AND WASHER IN A 1988 PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 63.
- 1) 30.1' NE TO THE NORTHEAST CORNER OF THE LOW WATER CROSSING
 - 2) 30.5' SE TO THE SOUTHEAST CORNER OF THE LOW WATER CROSSING
 - 3) 45.3' NW TO THE NORTHWEST CORNER OF THE LOW WATER CROSSING
 - 4) 46.2' SW TO THE SOUTHWEST CORNER OF THE LOW WATER CROSSING
 - 5) 11.05' SOUTH TO THE SOUND EDGE OF THE LOW WATER CROSSING
 - 6) 9.05' NORTH TO THE NORTH EDGE OF THE LOW WATER CROSSING
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,342.66' WEST TO THE 5/8" REBAR WITH A LYON COUNTY HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 30-18-12, AND THE P.O.B. OF THE 10.00 ACRE TRACT
 - 2) 1,571.66' WEST TO THE NORTHWEST CORNER OF THE 10.00 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25' SOUTH
 - 3) 2,685.32' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 30-18-12
 - 4) 1,330.08' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 30-18-12
 - 5) 2,660.16' SOUTH TO THE 1/2" IRON BAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 30-18-12

WEST QUARTER CORNER SECTION 29-18-12