

**WEST 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 29, TOWNSHIP 18 SOUTH,
RANGE 12 EAST**

- 1) G. M. WALKER, DEPUTY SURVEYOR, IN SURVEY NUMBER 35 RECORDED IN SURVEY BOOK "A" ON PAGES 69 & 70 DATED MAY 15, 1861 TO ESTABLISH THE CORNERS OF DAVID GILMORES LAND, BEING THE WEST 1/2 AND THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12, SAID THAT **HE SET A STONE MARKED "1/4/4"** FOR THE EAST 1/4/4 POST OF THE SOUTHWEST 1/4 OF SECTION 29-18-12 ON LINE AND HALFWAY BETWEEN THE STONE POST THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 29-18-12 AND THE STONE THAT HE SET FOR THE CENTER POST OF SECTION 29-18-12 ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.06 CHAINS SOUTH TO THE FOUND STONE SOUTH 1/4 POST OF SEC. 29-18-12
 - 2) 20.06 CHAINS NORTH TO THE STONE HE SET FOR THE CENTER POST OF SECTION 29-18-12
 - 3) 60.30 CHAINS NORTH TO THE FOUND STONE NORTH 1/4 POST OF SEC. 29-18-12
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 63 AT THE REQUEST OF PAUL G. WEAVER TO LOCATE THE CENTER OF SECTION 29-18-12 AND THE NORTHWEST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 29, AND THE NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 29, SAID THAT **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12 ON LINE AND HALFWAY BETWEEN THE 5/8" CAPPED REBAR THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-18-12 AND THE 5/8" CAPPED REBAR THAT HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-18-12 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS CONDUCTED IN MAY AND JUNE OF 1988 AND WAS FILED ON JUNE 29, 1988.

- 1) 12.05' NNW TO A PK NAIL & WASHER IN A FENCE POST
- 2) 5.05' WEST TO A PK NAIL & WASHER IN A FENCE POST
- 3) 5.0' WEST TO A LINE OF FENCE NORTH-SOUTH
- 4) 27.0' NE TO A 3" DIAMETER RED ELM TREE
- 5) 6' SOUTH TO THE CENTER OF A DRAINAGE AREA
- 7) SURVEY COORDINATES: N: 11427.374 E: 17146.623

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,326.40' SOUTH TO THE 5/8" REBAR HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-18-12
- 2) 1,326.40' NORTH TO THE 5/8" REBAR HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-18-12
- 3) 3,986.98' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 29-18-12
- 4) 2,651.51' WEST TO THE TRUE POSITION FOR THE NORTHWEST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 29-18-12—FALLS IN A CREEK

WEST SIXTEENTH CORNER SOUTHEAST QUARTER 29-18-12