

NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 30, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 49, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 48 DATED MAY 31 AND JUNE 4, 1870 TO ESTABLISH THE 1/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 30-18-12 AND THE 1/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 30-18-12, SAID THAT **HE SET A POST** FOR THE NORTH 1/2 CORNER OF THE NORTHEAST 1/4 OF SECTION 30-18-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-18-12 AND THE STONE THAT HE FOUND "DOWN" AT THE NORTH 1/4 CORNER SECTION 30-18-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-18-12
 - 2) 1,323' WEST TO THE STONE HE FOUND "DOWN" AT THE NORTH 1/4 CORNER OF SECTION 30-18-12
 - 3) 5,329' SOUTH TO THE POST HE SET FOR THE SOUTH 1/2 CORNER OF THE SE1/4 OF SECTION 30-18-12
-
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 2, 2010 FOR PROJECT NUMBER 10029-02, SURVEY F19003 IN THE SURVEY FILE FOR TOWNSHIP 18-12, SAID THAT **HE FOUND A 1/2" REBAR WITH HIS "LS 752" CAP** AT THE SOUTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 19-18-12 FROM A RETRACEMENT OF HIS SURVEY DATED 12-29-1989 FOR JOB NUMBER 89304.
 - 1) 19.60' NNW TO THE TOP CENTERLINE OF THE EAST END OF AN 18" IRON PIPE
 - 2) 36.50' WNW TO THE TOP CENTERLINE OF THE WEST END OF AN 18" IRON PIPE
 - 3) IN LINE WITH THE FENCE RUNNING NORTH EXTENDED
 - 4) 2.0' SOUTH TO THE CENTERLINE OF THE TRAVELED WAY OF ROAD 210 EAST-WEST
 - 5) 3.5' WEST TO A LINE OF POWER POLES RUNNING NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327.63' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 19-18-12
- 2) 1,327.64' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 19-18-12
- 3) 2,649.60' NORTH TO THE 1/2" REBAR HE FOUND [GOULD] AT THE NORTHEAST CORNER OF THE W1/2 SE1/4 OF SECTION 19-18-12

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 30-18-12