

WEST 1/4 CORNER SECTION 30, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 70 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 11" X 4"** FOR THE WEST 1/4 CORNER OF SECTION 30-18-12 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 12, 1856.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-18-12
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-18-12

- 2) G. M. WALKER, DEPUTY SURVEYOR, IN SURVEY NUMBER 36 RECORDED IN SURVEY BOOK "A" ON PAGES 70 & 71 DATED MAY 16, 1861 TO ESTABLISH THE CENTER POST OF SECTION 30-18-12, SAID THAT **HE FOUND THE STONE WEST 1/4 POST** OF SECTION 30-18-12 ON THE RANGE LINE ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 35.68 CHAINS EAST TO THE STONE HE SET FOR THE CENTER POST OF SECTION 30-18-12
 - 2) 76.00 CHAINS EAST TO THE FOUND STONE EAST 1/4 POST OF SEC. 30-18-12

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 29, AN **AGREEMENT SURVEY** REQUESTED BY J. M. KNOX TO LOCATE THE SOUTHWEST CORNER, SOUTH 1/4 CORNER, AND SOUTHEAST CORNER OF SECTION 19-18-12 RECORDED IN SURVEY BOOK "E" ON PAGE 29 DATED MAY 8, 1884, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 30-18-12 ON THE RANGE LINE. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 19-18-12 TO SET A STONE FOR THE SOUTHWEST CORNER OF SECTION 19-18-12 ON THE RANGE LINE ON THIS **AGREEMENT SURVEY**. THIS SURVEY WAS RECORDED IN VOLUME 41 ON PAGE 17 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 29, 1887 AND SURVEY F19002 IN THE SURVEY FILE FOR TOWNSHIP 18-12.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,639.5' NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE SOUTHWEST CORNER OF SECTION 19-18-12
 - 2) 5,279.0' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 19-18-12

- 4) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 73
ON DECEMBER 5, 1921 A PETITION SIGNED BY F. E. SUTTON AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 18-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON JANUARY 6, 1922, AND THE FINAL ORDER WAS ISSUED ON FEBRUARY 6, 1922 TO **VACATE** THE ROAD AS FOLLOWS:
 - 1) BEGINNING AT THE NORTHEAST CORNER OF SECTION 25-18-11; THENCE SOUTH ONE-HALF MILE AND ENDING AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 25-18-11

- 5) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 93
ON JULY 24, 1926 A PETITION SIGNED BY GEORGE SCHAEFER AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 18-12 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON SEPTEMBER 11, 1926, AND THE FINAL ORDER WAS ISSUED ON OCTOBER 8, 1926 TO **VACATE** THE ROAD AS FOLLOWS:
 - 2) BEGINNING AT THE SOUTHEAST CORNER OF SECTION 25-18-11; THENCE NORTH TO THE CENTER OF SECTION 25 [EAST 1/4 CORNER SECTION 25-18-11]

- 6) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 724 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 82 PETITIONED BY GEORGE SHAFER AND OTHERS TO VACATE A ROAD IN SECTION 25-18-11 THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND COUNTY SURVEYOR ON OCTOBER 8, 1926, AND WAS RECOMMENDED BY THE VIEWERS THAT THE ROAD SHOULD BE VACATED AS PETITIONED FOR AS THERE SEEMS TO BE NO DEMAND FOR THE ROAD AT THIS LOCATION. ALSO THE VIEWERS FOUND THAT MOST ALL OF THOSE RESIDING IN THE VICINITY OF THE ROAD ARE FAVORABLE TO THE VACATION OF THE ROAD AS PETITIONED FOR AND AT THE TIME SET AND VIEW MADE NO ONE APPEARED OR OBJECTED TO THE VACATION OF THE ROAD AS NOTED BY FRED FOWLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS.
THE FOLLOWING ROAD WAS VACATED:
BEGINNING AT THE SOUTHEAST CORNER OF SECTION 25-18-11; THENCE NORTH TO THE CENTER OF SECTION 25 [EAST 1/4 CORNER OF SECTION 25-18-11]
- 7) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, DEPUTY, IN AN INFORMAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 13 FOR AN INFORMAL ROAD SURVEY FOR A 50 FOOT WIDE ROAD RUNNING WEST FROM THE CENTER CORNER OF SECTION 30 -18-12 TO INTERSECT THE BURLINGAME ROAD, SAID THAT **HE SET A 3/4" SQUARE REBAR** FOR THE WEST 1/4 CORNER OF SECTION 30-18-12 ON THE RANGE LINE MIDWAY BETWEEN THE IRON PIN THAT HE FOUND THAT WAS SET FOR THE RURAL ELECTRIFICATION ASSOCIATION AT THE NORTHWEST CORNER OF SECTION 30-18-12 AND AT THE POINT MIDWAY BETWEEN THE FENCES EAST AND WEST AT THE SOUTHWEST CORNER OF SECTION 30-18-12 ON THIS INFORMAL SURVEY. THERE IS NO DATE RECORDED ON THIS INFORMAL SURVEY.
HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
1) 2,641.25' NORTH ON THE RANGE LINE TO THE IRON PIN SET BY THE RURAL ELECTRIFICATION ASSOCIATION HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-18-12
2) 2,641.25' SOUTH ON THE RANGE LINE TO A POINT MIDWAY BETWEEN THE FENCES EAST & WEST AT THE SOUTHWEST CORNER OF SECTION 30-18-12
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 63 TO LOCATE AND PERMANENTLY ESTABLISH THE CENTER CORNER OF SECTION 29-18-12, THE NORTHWEST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12, AND THE NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12 PETITIONED BY PAUL G. WALKER, RECORD OWNER OF THE SOUTHEAST 1/4 AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12 THAT BEGAN ON MAY 10, 1988 AND CONTINUED UNTIL COMPLETED ON JUNE 29, 1988, SAID THAT HE EXCAVATED FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 30-18-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **LOST** OR **OBLITERATED**. HE DID **NOT** RESET THE WEST 1/4 CORNER OF SECTION 30-18-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

WEST QUARTER CORNER SECTION 30-18-12