

**NORTH 1/4 CORNER SECTION 32, TOWNSHIP 18 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 502 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 8" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-18-12.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.93 CHAINS WEST TO THE 25" X 18" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-18-12
  - 2) 39.92 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 28, 32 & 33-18-12
  
- 2) G. M. WALKER, DEPUTY SURVEYOR, IN SURVEY NUMBER 35 RECORDED IN SURVEY BOOK "A" ON PAGES 69 & 70 DATED MAY 15, 1861 TO ESTABLISH THE CORNERS OF DAVID GILMORES LAND, BEING THE WEST 1/2 AND THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12, SAID THAT **HE FOUND THE STONE SOUTH 1/4 POST** OF SECTION 29-18-12 ON THIS SURVEY.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 20.03 CHAINS WEST TO THE STONE HE SET FOR THE S1/4/4 POST OF THE SW1/4 OF SECTION 29-18-12
  - 2) 40.06 CHAINS WEST TO THE STONE POST HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-18-12
  - 3) 20.06 CHAINS NORTH TO THE STONE HE SET FOR THE E1/4/4 POST OF THE SW1/4 OF SECTION 29-18-12
  - 4) 40.12 CHAINS NORTH TO THE STONE HE SET FOR THE CENTER POST OF SECTION 29-18-12
  - 5) 80.36 CHAINS NORTH TO THE FOUND STONE NORTH 1/4 POST OF SEC. 29-18-12
  
- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-12 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 29-18-12" AND THE "NW CORNER NE1/4 SECTION 32-18-12".
  - 1) 24' NORTH TO A WITNESS [REA]
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 63 TO LOCATE AND PERMANENTLY ESTABLISH THE CENTER CORNER OF SECTION 29-18-12, THE NORTHWEST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12, AND THE NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12 PETITIONED BY PAUL G. WALKER, RECORD OWNER OF THE SOUTHEAST 1/4 AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 29-18-12 THAT BEGAN ON MAY 10, 1988 AND CONTINUED UNTIL COMPLETED ON JUNE 29, 1988, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER AND A COUNTY BACKHOE FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 29-18-12, BUT HE DID **NOT** FIND THE STONE. HE DETERMINED THAT THIS CORNER WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-18-12 ON LINE AND HALFWAY BETWEEN THE SOUTHWEST AND SOUTHEAST CORNERS OF SECTION 29-18-12 ON THIS **PERMANENT SURVEY**.
  - 1) 31.35' SSE TO A PK NAIL & WASHER IN A POWER POLE
  - 2) 27.85' NW TO A PK NAIL & WASHER IN A 18" HONEY LOCUST TREE
  - 3) 26.7' NNW TO A PK NAIL & WASHER IN A FENCE POST
  - 4) 8.25' EAST TO A LINE OF FENCE TO THE NORTH EXTENDED
  - 5) 3.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
  - 6) SURVEY COORDINATES: N: 10100.988 E: 17152.579HIS DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,657.50' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-18-12
  - 2) 2,657.50' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 29-18-12
  - 3) 1,326.40' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 29-18-12
  - 4) 2,652.80' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-18-12
  - 5) 5,313.38' NORTH TO THE 5/8" REBAR WITH A 1/2" REBAR HE SET OVER IT FOR THE NORTH 1/4 CORNER OF SECTION 29-18-12
- 5) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 1, 1996, FOR PROJECT NUMBER 96-5N, **FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 32-18-12 FROM THE TIES BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 63 AND FILED JUNE 29, 1988 IN THE COUNTY ENGINEERS OFFICE.
- 1) 31.60' SSE TO A PK NAIL & WASHER IN A POWER POLE
  - 2) 26.7' NNW TO A PK NAIL & WASHER IN A FENCE POST
  - 3) 9.0' EAST TO A LINE OF FENCE TO THE NORTH EXTENDED
  - 4) 62.0' WEST TO THE CENTERLINE OF A FIELD ENTRANCE TO THE NORTH
  - 5) 3.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 16, 2013 FOR PROJECT NUMBER 13250-02, A SURVEY OF FOUR TRACTS IN THE SOUTHWEST 1/4 OF SECTION 32-18-12 FOR DARLA EDWARDS, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 18-12, SAID THAT **HE FOUND THE 5/8" IRON PIN WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 32-18-12 FROM PREVIOUS REFERENCE TIES DONE BY WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, DATED AUGUST 1, 1996. HE HAD SET HIS IRON PIN IN HIS 1988 PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 63 IN THE COUNTY ENGINEERS OFFICE.
- 1) 31.60' SSE TO A PK NAIL & WASHER IN A POWER POLE
  - 2) 26.70' NNW TO A PK NAIL & WASHER IN A FENCE POST
  - 3) 9.0' EAST TO A LINE OF FENCE TO THE NORTH EXTENDED
  - 4) 62.0' WEST TO THE CENTERLINE OF A FIELD ENTRANCE TO THE NORTH
  - 5) 3.50' SOUTH TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 4,500.65' SOUTH TO THE 1/2" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET FOR THE NORTHEAST CORNER OF TRACT D
  - 2) 5,300.65' SOUTH TO THE 1/2" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 32-18-12 ON THE TOWNSHIP LINE

NORTH QUARTER CORNER SECTION 32-18-12