

CENTER CORNER SECTION 34, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 22, 1992, FOR JOB NUMBER 92277-02, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE CENTER CORNER OF SECTION 34-18-12.
 - 1) FALLS ON THE NORTH FACE OF A CORNER POST
 - 2) 40' EAST TO A LINE OF FENCE NORTH-SOUTH
 - 3) 70' SOUTH TO A LINE OF FENCE TO THE WEST
 - 4) AT THE INTERSECTION OF LINES FROM OPPOSITE 1/4 CORNERS

- 2) ROBERT J. BORSICK. L.S. 1180, OF BARTLETT & WEST ENGINEERS, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 12, 2006 FOR PROJECT NUMBER 15340-001, SAID THAT **HE FOUND THE 1/2" IRON BAR WITH A RED CAP STAMPED "LS 752"** AT THE CENTER CORNER OF SECTION 34-18-12 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE. THE FOLLOWING TIES ARE **HORIZONTAL TIES:**
 - 1) 8.24' SOUTH TO A MAG NAIL & WASHER IN THE TOP OF A BRACE POST
 - 2) 20.35' WEST TO A MAG NAIL & WASHER IN A BRACE POST
 - 3) 0.8' EAST TO A CORNER FENCE POST
 - 4) 29.40' WNW TO A MAG NAIL & WASHER IN A HEDGE TREE**HIS DRAWING SHOWS THE FOLLOWING INFORMATION:**
 - 1) 2,648.71' WEST TO THE 5/8" REBAR HE FOUND AT THE WEST 1/4 CORNER OF SECTION 34-18-12
 - 2) 2,652.66' NORTH TO THE STONE & REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 34-18-12
 - 3) 1,323.82' EAST TO THE 1/2" REBAR WITH "LS 667" CAP HE FOUND AT THE NORTH 1/16TH CORNER OF THE SE1/4 OF SECTION 34-18-12
 - 4) 2,646.94' EAST TO THE 1/2" REBAR WITH "LS 667" CAP HE FOUND AT THE EAST 1/4 CORNER OF SECTION 34-18-12
 - 5) 2,653.73' SOUTH TO THE DRILL HOLE IN A BRIDGE DECK HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 34-18-12

CENTER CORNER SECTION 34-18-12