

NORTH 1/4 CORNER SECTION 36, TOWNSHIP 18 SOUTH, RANGE 12 EAST

- 1) ON PAGE 489 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 28" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 36-18-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.81 CHAINS WEST TO THE 21" X 9" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-18-12
 - 2) 39.80 CHAINS EAST TO THE 21" X 21" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25 & 36-18-12 ON THE EAST TOWNSHIP BOUNDARY

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 14, 2001, FOR PROJECT NUMBER 00379-02, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 18-12 FOR THE SUBDIVISION OF SECTION 36-18-12, SAID THAT HE DEEMED THAT THE NORTH 1/4 CORNER OF SECTION 36-18-12 WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 36-18-12 IN LINE WITH THE HEDGE AND THE FENCE TO THE SOUTH, AND IN THE CENTER OF THE PUBLIC ROAD.
 - 1) 110.65' NE TO A 40 D NAIL & WASHER IN A POWER POLE
 - 2) 25.0' NORTH TO A LINE OF FENCE EAST-WEST
 - 3) 25.0' SOUTH TO A LINE OF FENCE EAST-WEST
 - 4) 20.4' SOUTH TO A CONCRETE NAIL & WASHER IN A 3' HEDGE TREE
 - 5) 33.2' SW TO THE BASE OF A STEEL POSTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,308.52' WEST TO THE THEORETICAL POSITION FOR THE NORTH 1/16TH CORNER OF THE NW1/4 OF SECTION 36-18-12
 - 2) 2,617.04' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF SECTION 36-18-12
 - 3) 2,622.77' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-18-12 ON THE RANGE LINE
 - 4) 1,324.59' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/16TH CORNER OF THE NW1/4 OF SECTION 36-18-12
 - 5) 2,649.19' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 36-18-12
 - 6) 5,297.76' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 36-18-12 ON THE TOWNSHIP LINE, WHERE REMAINS OF THE STONE WERE FOUND

NORTH QUARTER CORNER SECTION 36-18-12