

**WEST 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 36, TOWNSHIP 18 SOUTH,  
RANGE 12 EAST**

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 15, 2001, FOR PROJECT NUMBER 00379-02, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 18-12 FOR THE SUBDIVISION OF SECTION 36-18-12, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 36-18-12 ON TRUE LINE AND HALF WAY BETWEEN THE NORTH QUARTER CORNER AND THE CENTER CORNER OF SECTION 36-18-12.
  - 1) 33.4' NW TO AN ELM TREE
  - 2) 47.5' NORTH TO A SPLIT ELM TREE
  - 3) 10.4' SE TO A 24" WILLOW TREE
  - 4) 1.0' WEST TO A LINE OF FENCE TO THE NORTH
  - 5) 0.5' NORTH TO A LINE OF FENCE EAST-WEST

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

  - 1) 1,324.59' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 36-18-12
  - 2) 1,324.59' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 36-18-12
  - 3) 3,973.17' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 36-18-12 ON THE TOWNSHIP LINE WHERE REMAINS OF THE STONE WERE FOUND
  - 4) 1,310.91' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER CORNER OF THE NORTHWEST 1/4 OF SECTION 36-18-12
  - 5) 2,621.83' WEST TO THE THEORETICAL POSITION FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 36-18-12

WEST SIXTEENTH CORNER NORTHEAST QUARTER 36-18-12