

NORTH 1/4 CORNER SECTION 04, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 92 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 3"** FOR THE NORTH 1/4 CORNER OF SECTION 4-18-13 ON THE TOWNSHIP LINE ON DECEMBER 29, 1855.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-18-13
 - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-18-13

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 28 OF THE 8TH TERM DATED JUNE 25, 2874, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 83 TO ESTABLISH THE PERMANENT CENTER CORNER OF SECTION 33-17-13 AND TO SUBDIVIDE THE NORTHEAST 1/4 INTO THE EAST 1/2 AND TO ESTABLISH THE NORTHWEST AND THE SOUTHWEST 1/4/4'S, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-17-13 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 71 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 128 DATED APRIL 26, 1875 TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 4-18-13, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 4-18-13 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. THE SURVEY WAS NOT SIGNED AND DID NOT APPEAR TO HAVE BEEN COMPLETED.

- 4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 135 ON THE LEFT PAGE DATED APRIL 4, 1882 FOR STRATTON TO FIND THE DIMENSIONS OF A 99.92 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 4-18-13, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 4-18-13 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.33 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 4-18-13
 - 2) 39.65 CHAINS SOUTH ON THE 1/2 SECTION LINE TO THE RAILROAD FENCE

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 24, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 205 DATED MAY 13 & 14, 1901 ORDERED BY CHARLES BROWER TO LOCATE THE SOUTHEAST AND SOUTHWEST CORNERS OF SECTION 34-17-13, SAID THAT HE DID **NOT** FIND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 33-17-13 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 2. SEE ALSO PACKET "M 28" IN MISCELLANEOUS DRAWER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS SURVEY.

NORTH QUARTER CORNER 04-18-13