

NORTH 1/4 CORNER SECTION 05, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 92 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 10" X 3"** FOR THE NORTH 1/4 CORNER OF SECTION 5-18-13 ON THE TOWNSHIP LINE ON DECEMBER 29, 1855.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-18-13
 - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-18-13

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 24, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 205 DATED MAY 13 & 14, 1901 ORDERED BY CHARLES BROWER TO LOCATE THE SOUTHEAST AND SOUTHWEST CORNERS OF SECTION 34-17-13, SAID THAT HE DID **NOT** FIND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 32-17-13 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 2. SEE ALSO PACKET "M 28" IN MISCELLANEOUS DRAWER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS SURVEY.

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SURVEY DATED FEBRUARY 17, 1998, FOR PROJECT NUMBER 98030-02 AND FILED AS SURVEY F32001 IN THE SURVEY FILE FOR 17-13, SAID THAT HE SEARCHED FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 32-17-13, BUT DID **NOT** FIND THE STONE. HE SAID THAT THIS CORNER WAS NOT FOUND BY ALVA J. SMITH IN 1904. HE CONSIDERED THAT THIS CORNER WAS **LOST**. HE DID **NOT** RESET THE SOUTH 1/4 CORNER OF SECTION 32-17-13 ON THE TOWNSHIP LINE ON THIS SURVEY.

NORTH QUARTER CORNER 05-18-13