

NORTHWEST CORNER SECTION 06, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 92 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 15" X 4"** FOR THE CORNER TO TOWNSHIPS 17 & 18 SOUTH, RANGES 12 & 13 EAST AT THE NORTHWEST CORNER OF SECTION 6-18-13 ON DECEMBER 27, 1855.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 38.97 CHAINS EAST ON THE TOWNSHIP LINE TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 6-18-13
 - 2) 39.07 CHAINS EAST ON THE TOWNSHIP LINE TO INTERSECT THE WEST BOUNDARY OF THE SAC & FOX RESERVATION LANDS
 - 3) 78.97 CHAINS EAST ON THE TOWNSHIP LINE TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-18-13
 - 4) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 19" X 11" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-18-13
 - 5) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-18-13

- 2) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 26 FOR THE "FOREST HILL TO WATERLOO ROAD" [PACKET 164 I THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT WAS SURVEYED MARCH 15 & 16, 1859 AND ESTABLISHED ON APRIL 4, 1959 IN COMMISSIONERS JOURNAL ON PAGE 59, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 1-18-12 AT THE TOWNSHIP CORNER ON THE RANGE LINE ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 13-17-12 AT A TURN TO THE NORTHEASTERLY TO THE SOUTH LINE OF WATERLOO TOWNSITE
 - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE EAST 1/4 CORNER OF SECTION 36-18-12 AT A TURN TO THE SOUTHWESTERLY TO THE NORTH 1/4 CORNER OF SECTION 1-19-12 AT A TURN TO THE SOUTH ON THE 1/2 SECTION LINE TO THE NORTH 1/4 CORNER OF SECTION 12-19-12 AT THE NORTHEAST CORNER OF THE TOWN OF FOREST HILL TO COMMENCE THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN AN **AGREEMENT SURVEY** TO ESTABLISH THE CORNERS OF SECTION 36-17-12 DATED APRIL 6 & 7, 1880 AND RECORDED IN THE REGISTER OF DEEDS OFFICE ON MAY 29, 1880, SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 17-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 36-17-12 AT THE TOWNSHIP CORNER ON THIS **AGREEMENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.96 CHAINS WEST ON THE TOWNSHIP LINE TO THE ROCK HE SET FOR THE SOUTH 1/16TH CORNER OF THE SE1/4 OF SECTION 36-17-12
 - 2) 39.92 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AND **HE RESET** FOR THE SOUTH 1/4 CORNER OF SECTION 36-17-12
 - 3) 59.88 CHAINS WEST ON THE TOWNSHIP LINE TO THE ROCK HE SET FOR THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 36-17-12
 - 4) 79.84 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-17-12
 - 5) 19.98 CHAINS NORTH ON THE RANGE LINE TO THE ROCK HE SET FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 36-17-12
 - 6) 39.96 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 36-17-12

HIS INFORMATION IS CONTINUED ON PAGE 2

- 7) 59.94 CHAINS NORTH ON THE RANGE LINE TO THE ROCK HE SET FOR THE EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 36-17-12
 - 8) 79.92 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-12
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 68, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 147 DATED MARCH 3, 1903 FOR MARY D. COULSON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 36-17-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FAILED TO FIND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 36-17-12 AT THE TOWNSHIP CORNER ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 118 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 74" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
 - 5) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 55
ON OCTOBER 2, 1918 A PETITION SIGNED BY SILAS DAVIS AND OTHERS FOR THE WIDENING OF A ROAD IN TOWNSHIPS 17-12 AND 17-13 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON NOVEMBER 11, 1918, AND THE FINAL ORDER WAS ISSUED ON JANUARY 10, 1919.
 - 1) VIEWERS REPORT: WE BELIEVE WITH THE IMPORTANCE OF THIS ROAD AND NUMEROUS GULLIES TO BE CROSSED AND HILLS THAT SHOULD BE CUT DOWN, WHICH WILL REQUIRE SUCH WIDTH TO PROPERLY GRADE, WE RECOMMEND THAT THE ROAD BE WIDENED TO 60 FEET FROM THE WEST PART OF READING EXTENDING WEST TO THE WEST LINE OF SECTION 2-18-12.
 - 2) THE BALANCE OF THE ROAD PETITIONED TO REMAIN AS IS PRESENTLY ESTABLISHED
 - 6) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 709 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 66 PETITIONED BY SILAS DAVIS AND OTHERS FOR THE WIDENING OF A ROAD IN TOWNSHIPS 28-12 AND 18-13 THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON NOVEMBER 11, 1919 AND WAS ORDERED THAT THE ROAD BE WIDENED TO 60 FEET FROM THE WEST LINE OF READING CITY EXTENDING WEST TO THE WEST LINE OF SECTION 2-18-12, THE BALANCE TO REMAIN AS PRESENT ESTABLISHED ON NOVEMBER 11, 1919 AS NOTED BY FRANK McCAIN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS. THE *RETURN OF SURVEY AND PLAT* DOES NOT MATCH THE DESCRIPTION OF THE ROAD WIDENING ALLOWED. HE APPARENTLY **FOUND** THE NORTHWEST CORNER OF SECTION 2-18-12 ON THE TOWNSHIP LINE ON THE ROAD WIDENING ALLOWED.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE ROAD WIDENING EXTENDS EAST ON THE TOWNSHIP LINE FOR 4-1/2 MILES TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 34-17-13 ON THE WEST LINE OF READING CITY TO BEGIN THE ROAD WIDENING ALLOWED
 - 2) THE ROAD WIDENING EXTENDS WEST ON THE TOWNSHIP LINE FOR 1 MILE TO THE NORTHWEST CORNER OF SECTION 2-18-12 AT THE TERMINUS OF THE ROAD WIDENING ALLOWED
 - 7) THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP SHOWS A **STONE AND PIN** AT THE NORTHWEST CORNER OF SECTION 6-18-13 AT THE TOWNSHIP CORNER. THERE ARE NO TIES TO THE STONE ON THIS PAGE.

CONTINUED ON PAGE 3

- 8) IN GREEN DIETZGEN FIELD BOOK NUMBER 14 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE LABELED "JACOBS CREEK BRIDGE" ON PAGE 54 IT SHOWS A **STONE & IRON PIN** AT THE NORTHWEST CORNER OF SECTION 6-18-13 AT THE TOWNSHIP CORNER. THERE ARE NO TIES TO THE CORNER ON THIS PAGE.

NORTHWEST CORNER SECTION 06-18-13