

NORTH 1/4 CORNER SECTION 10, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 639 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 8" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-18-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS WEST TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-18-13
 - 2) 39.95 CHAINS EAST TO THE 24" X 18" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-18-13 ON THE COUNTY LINE

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE OF PAGE 151 DATED MARCH 11, 1878, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 10-18-13 ON THIS ROAD SURVEY. NO WIDTH IS RECORDED.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES UNTIL IT INTERSECTS WHAT IS KNOWN AS CHESTNUT STREET IN THE TOWN OF READING AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 10-18-13, THEN EXTENDS WEST ON THE SECTION LINES FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 15-18-13, THEN EXTENDS SOUTH ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-18-13, THEN WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-18-13, THEN SOUTH ON THE SECTION LINES FOR 4 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-19-13 TO COMMENCE THIS ROAD SURVEY

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F03012 IN THE SURVEY FILE FOR TOWNSHIP 18-13 FOR AN 8.5 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 3-18-13 FOR DENNIS HODGES, PROJECT NUMBER 06065-02 DATED FEBRUARY 22, 2006, SHOWS ON HIS SURVEY DRAWING THAT HE HAD EXCAVATED FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 3-18-13 PREVIOUSLY, BUT HE DID **NOT** FIND THE STONE. HE DETERMINED A **THEORETICAL POSITION** FOR THE SOUTH 1/4 CORNER OF SECTION 3-18-13, BUT HE DID **NOT** RESET THIS CORNER AT THIS TIME.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,639.94' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 3-18-13
 - 2) 1,078.69' EAST TO THE 1/2" REBAR WITH HIS "LS 752" HE SET ON THE SECTION LINE AT THE INTERSECTION OF ROAD "Y7"/CHESTNUT STREET EXTENDED
 - 3) 2,639.94' EAST TO THE 3/4" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 3-18-13 ON THE LYON AND OSAGE COUNTY LINE

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 13, 2010 FOR PROJECT NUMBER 10161-02, SURVEY F03013 IN THE SURVEY FILE FOR TOWNSHIP 18-13 FOR A SURVEY OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 3-18-13 FOR WILKERSON, SAID THAT HE CONSIDERED THAT THE SOUTH 1/4 CORNER OF SECTION 3-18-13 WAS **LOST**. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 3-18-13 ON TRUE LINE AND HALFWAY BETWEEN THE SOUTHWEST CORNER OF SECTION 3-18-13 AND THE SOUTHEAST CORNER OF SECTION 3-18-13 ON THE LYON AND OSAGE COUNTY LINE.

- 1) 26.35' SSE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 2) 10.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 240 EAST-WEST
- 3) 38.90' NNW TO A SPIKE & BOTTLECAP IN THE TOP OF A BRACE POST
- 4) 35.0' NORTH TO A LINE OF FENCE TO THE EAST
- 5) 6.0' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "Y5" TO THE SOUTH
- 6) THE CORNER FALLS ON THE SOUTH EDGE OF THE TRAVELED WAY

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.97' EAST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 3-18-13
- 2) 2,639.94' EAST TO THE 3/4" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 3-18-13 ON THE LYON AND OSAGE COUNTY LINE
- 3) 2,639.94' WEST TO THE 5/8" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 3-18-13
- 4) 1,321.03' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 3-18-13
- 5) 1,981.55' NORTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF THE SE1/4 OF SECTION 3-18-13 AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 24.30' WEST ON THE EASTERLY RIGHT-OF-WAY LINE OF BROAD STREET
- 6) 2,642.07' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 3-18-13
- 7) 5,271.47' NORTH TO THE 3/4" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 3-18-13 ON THE TOWNSHIP LINE

NORTH QUARTER CORNER 10-18-13