

WEST 1/4 CORNER SECTION 10, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 638 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 4"** FOR THE 1/4 CORNER BETWEEN SECTION 9 & 10-18-13.

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 125 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 86 TO 88 PETITIONED BY WILLIAM H. DOUGLASS AND OTHERS FOR THE **VACATION** AND LOCATION OF COUNTY ROADS IN TOWNSHIP 18-13 [PACKET 369 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 25, 1881, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JULY 8, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 13, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 10-18-13 AT THE TERMINUS OF THE ROAD LOCATED ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS LOCATED ROAD EXTENDS EAST ON THE 1/2 SECTION LINE FOR 2,640 FEET TO THE CENTER CORNER OF SECTION 10-18-13 TO COMMENCE THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 218 DATED JUNE 25, 1881, FOR A ROAD SURVEY IN TOWNSHIP 18-13 APPARENTLY **FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 10-18-13 AT THE TERMINUS OF THIS ROAD LOCATION SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS LOCATED ROAD EXTENDS EAST ON THE 1/2 SECTION LINE FOR 2,640' TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 10-18-13 TO COMMENCE THIS ROAD SURVEY

WEST QUARTER CORNER 10-18-13