

EAST 1/4 CORNER SECTION 15, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 635 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 15 ON THE COUNTY LINE ON OCTOBER 17, 1860.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE COUNTY LINE TO THE 18" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-18-13
- 2) 40.00 CHAINS SOUTH ON THE COUNTY LINE TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-18-13
- 2) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 72 DATED NOVEMBER 7, 1883 FOR A ROAD IN TOWNSHIP 18, RANGE 13 FOR W. SOUTHWORTH, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 15-18-13 ON THE LYON AND OSAGE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS 60 FOOT WIDE ROAD EXTENDS NORTH ON THE COUNTY LINE FOR 13.41 CHAINS TO A STONE HE SET; THEN CONTINUES NORTH ON THE COUNTY LINE AS AN 80 FOOT WIDE ROAD FOR 11.00 CHAINS TO A STONE HE SET AT 24.41 CHAINS NORTH OF THE EAST 1/4 CORNER OF SECTION 15-18-13; THEN CONTINUES NORTH ON THE COUNTY LINE AT 60 FEET WIDE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 15-18-13 TO BEGIN THIS ROAD SURVEY
- 2) THIS 60 FOOT WIDE ROAD CONTINUES SOUTH ON THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-18-13 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY ARTHUR E. MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 255 IN RECORDED ROAD RECORD BOOK "B" ON PAGES 606 TO 608 PETITIONED BY WILLIAM SOUTHWORTH AND OTHERS FOR A COUNTY ROAD ON THE LYON AND OSAGE COUNTY LINE IN TOWNSHIP 18-13 [PACKET 486 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 7, 1883, WAS ESTABLISHED AS 60 FOOT WIDE ROAD. **EXCEPT** AS SPECIFIED IN THE FIELD NOTES, ON JANUARY 10, 1884, AS NOTED BY J. E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON FEBRUARY 4, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 15-18-13 ON THE LYON AND OSAGE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 3) THIS 60 FOOT WIDE ROAD EXTENDS NORTH ON THE COUNTY LINE FOR 13.41 CHAINS TO A STONE HE SET; THEN CONTINUES NORTH ON THE COUNTY LINE AS AN 80 FOOT WIDE ROAD FOR 11.00 CHAINS TO A STONE HE SET AT 24.41 CHAINS NORTH OF THE EAST 1/4 CORNER OF SECTION 15-18-13; THEN CONTINUES NORTH ON THE COUNTY LINE AT 60 FEET WIDE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 15-18-13 TO BEGIN THIS ROAD SURVEY
- 4) THIS 60 FOOT WIDE ROAD CONTINUES SOUTH ON THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-18-13 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) TIES RECEIVED OCTOBER 3, 1996, FROM THE OSAGE COUNTY HIGHWAY DEPARTMENT, SHOW A “**MONUMENT**” AT THE WEST 1/4 CORNER OF SECTION 14-18-13 ON THE LYON AND OSAGE COUNTY LINE, BUT GIVES NO DESCRIPTION OF THE MONUMENT OR THE DATE. **[NOTE: CHECK FOR THE STONE OF RECORD BEFORE ACCEPTING ANY MONUMENT AS THE CORNER!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- 1) 28.4' EAST TO A LINE FENCE POST
 - 2) 30.2' SE TO A GATE POST
 - 3) 29.5' WEST TO A FENCE

EAST QUARTER CORNER 15-18-13