

**WEST 1/4 CORNER SECTION 16, TOWNSHIP 18 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 641 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 17-18-13 ON OCTOBER 19, 1860.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-18-13
- 2) 40.00 CHAINS SOUTH TO THE 24" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-18-13
- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 147 AT THE REQUEST OF B. F. PRICE OF READING, KANSAS TO LOCATE THE SOUTH LINE OF SECTION 29-18-13 AND EAST LINES OF SECTIONS 20 AND 29-18-13, SAID THAT HE DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 16-18-13 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 9-18-13 SOUTH TO THE 3/4" DEMETER IRON BAR THAT HE SET FOR THE NORTHEAST CORNER OF SECTION 20-18-13. HE DID **NOT** RESET THE WEST 1/4 CORNER OF SECTION 16-18-13 ON THIS **INFORMAL SURVEY**.

- 3) STEVEN S. BROSEMER, L.S. 752, IN SURVEY F16001 IN THE SURVEY FILE FOR TOWNSHIP 18-13 FOR THE SURVEY OF A 7 ACRE TRACT IN THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 16-18-13 FOR HIS PROJECT NUMBER 87130 DATED JULY 17, 1987, SAID IN HIS *REPORT OF SURVEY* THAT HE EXCAVATED WITH A COUNTY MOTOR GRADER AND BACKHOE FOR THE GLO STONE OF RECORD AT THE WEST 1/4 CORNER OF SECTION 16-18-13, BUT THE STONE WAS **NOT** RECOVERED. HE DEEMED THAT THIS CORNER WAS **LOST** AND HE SET A **1/2" X 24" REBAR WITH HIS PLASTIC "BROSEMER LS 752" CAP** FOR THE WEST 1/4 CORNER OF SECTION 1-18-13 ON LINE AND HALFWAY BETWEEN THE NORTHWEST AND SOUTHWEST CORNERS OF SECTION 16-19-13. HE NOTED ON HIS SURVEY THAT THIS SECTION CORNER IS ALSO THE NORTHWEST CORNER OF THE 7 ACRE TRACT.

- 1) 1/2" X 24" REBAR WITH PLASTIC CAP STAMPED "BROSEMER LS 752" CAP SET FOR THE WEST 1/4 CORNER OF SECTION 16-18-13
- 2) 2.7' EAST TO THE CENTER OF THE TRAVELED WAY OF THE ROAD NORTH-SOUTH
- 3) 28.0' EAST TO A LINE OF FENCE TO THE NORTH
- 4) 20.0' WEST TO A LINE OF NORTH-SOUTH FENCE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 502' SOUTH TO THE 1/2" X 24" REBAR WITH HIS PLASTIC "BROSEMER LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 7 ACRE TRACT, AS WITNESSED BY THE 1/2" X 24" REBAR WITH HIS PLASTIC "BROSEMER LS 752" CAP HE SET AT 30' EAST ON THE EAST ROAD RIGHT-OF-WAY LINE
- 2) 2,636.35' SOUTH TO THE GLO STONE HE FOUND LAID OVER AT THE SOUTHWEST CORNER OF SECTION 16-18-13 THAT **HE RESET** WITH A 1/2" X 24" REBAR WITH HIS PLASTIC "BROSEMER LS 752" CAP
- 3) 2,636.36' NORTH TO THE GLO STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 16-18-13 WITH 1/2" X 24" REBARS WITH HIS PLASTIC "BROSEMER LS 752" CAPS ON THE EAST AND WEST SIDES OF THE STONE
- 4) 30' EAST TO THE 1/2" X 24" REBAR WITH HIS PLASTIC "BROSEMER LS 752" CAP HE SET ON THE EAST ROAD RIGHT-OF-WAY

HIS INFORMATION IS CONTINUED ON PAGE 2

- 5) 608' EAST TO THE 1/2" X 24" REBAR WITH HIS PLASTIC "BROSEMER LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 7 ACRE TRACT
- 6) 5.352.10' EAST TO THE 1/2" X 24" REBAR WITH HIS PLASTIC "BROSEMER LS 752" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 16-19-13

WEST QUARTER CORNER 16-18-13