

NORTH 1/4 CORNER SECTION 17, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 647 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 8 & 17-18-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 17" X 15" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-18-13
 - 2) 40.00 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THE SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-18-13

- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN INFORMAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 147 AT THE REQUEST OF B. F. PRICE OF READING, KANSAS TO LOCATE THE SOUTH LINE OF SECTION 29-18-13 AND EAST LINES OF SECTIONS 20 AND 29-18-13, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE NORTH 1/4 CORNER OF SECTION 17-18-13 ON THIS INFORMAL SURVEY.
 - 1) 20' NORTH TO A FENCE

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-13 SHOWS A **STONE** AT THE "SW CORNER SE1/4 SECTION 8-18-13".
 - 1) 20' NORTH OF A FENCE NEAR A DOUBLE FENCE POST AND BRACE

NORTH QUARTER CORNER 17-18-13