

WEST 1/4 CORNER SECTION 17, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 647 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 18-18-13.

- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 147 AT THE REQUEST OF B. F. PRICE OF READING, KANSAS TO LOCATE THE SOUTH LINE OF SECTION 29-18-13 AND EAST LINES OF SECTIONS 20 AND 29-18-13, SAID THAT HE DID **NOT** FIND THE STONE AT THE WEST CORNER OF SECTION 17-18-13 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 17-18-13 SOUTH TO THE STONE THAT HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 20-18-13. HE DID **NOT** RESET THE WEST 1/4 CORNER OF SECTION 17-18-13 ON THIS **INFORMAL SURVEY**.

WEST QUARTER CORNER 17-18-13