

WEST 1/4 CORNER SECTION 18, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 91 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 10" X 3-1/2"** FOR THE WEST 1/4 CORNER OF SECTION 18-18-13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 27, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-18-13
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 14" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-18-13
- 2) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 47 [PACKET 397 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED JULY 1864 FOR THE "FOREST HILL & WATERLOO ROAD", SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 13-18-12 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY.
- 3) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1863, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 80 AND DATED APRIL 1864, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 18-18-13 ON THE RANGE LINE ON THIS ROAD SURVEY.
- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 85 AT THE ORDERED BY EDWIN D. JONES TO PERMANENTLY ESTABLISH THE NORTHEAST CORNER OF SECTION 13-18-12, THE 1/4 CORNER BETWEEN SECTIONS 12 & 13, THE 1/4 CORNER BETWEEN SECTION 13 & 14, AND SUCH OTHER CORNERS OF SAID SECTION 13 AS MAY BE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE SET A 24" X 14" X 10" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 13-18-12 ON THE RANGE LINE AT HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 13-18-12 AND THE STONE THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 13-18-12 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS MADE UPON THE 5TH, 6TH, 7TH AND 8TH OF JUNE, 1911 AND ENTERED ON AUGUST 19, 1911. SEE ALSO PACKET "M 167" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,643'-3" NORTH ON THE RANGE LINE TO THE 20" X 3" X 6" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 13-18-12
 - 2) 2,643'-3" SOUTH ON THE RANGE LINE TO THE 18" X 8" X 6" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 13-18-12
- 5) IN GREEN DIETZGEN FIELD BOOK NUMBER 14 LABELED "JACOBS CREEK BRIDGE" ON PAGE 54 IT SHOWS A **STONE** AT THE WEST 1/4 CORNER OF SECTION 18-18-13 ON THE RANGE LINE.
- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-12 SHOWS A **STONE** AT THE "SE CORNER NE1/4 SECTION 13-18-12" ON THE RANGE LINE.
- 1) 38.8' WEST TO THE BASE OF A CATALPA TREE
 - 2) 27.3' EAST TO THE BASE OF A 10" OSAGE TREE

CONTINUED ON PAGE 2

- 7) KRETSINGER REFERENCE TIE BOOK NUMBER 13 ON PAGE 45 AT THE TOP OF THE PAGE SHOWS A **STONE** AT THE "E1/4 CORNER SECTION 13-18-12" ON THE RANGE LINE.
 - 1) 27.3' EAST TO THE BASE OF A 10" HEDGE TREE
 - 2) 38.3' WEST TO THE BASE OF A 10" CATALPA TREE

- 8) THE KRETSINGER REFERENCE TIE BOOKS FOR TOWNSHIP 18-13 SHOWS A **STONE** AT THE "W1/4 CORNER SECTION 18-18-13" ON THE RANGE LINE.
 - 1) 28.7' NE TO THE NORTH GATE POST
 - 2) 21.6' WEST TO THE SOUTH GATE POST
 - 3) 28.3' ENE TO A SPIKE IN A HEDGE STUMP

WEST QUARTER CORNER SECTION 18-18-13