

**NORTHEAST CORNER SECTION 22, TOWNSHIP 18 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 635 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-18-13 ON THE COUNTY LINE ON OCTOBER 17, 1860.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH ON THE COUNTY LINE TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 23-18-13
  - 2) 80.00 CHAINS SOUTH ON THE COUNTY LINE TO THE 20" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-18-13
  - 3) 40.25 CHAINS WEST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-18-13
  - 4) 80.50 CHAINS WEST TO THE 24" X 15" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-18-13
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 2 AND DATED MAY 1882, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 22-18-13 ON THE LYON AND OSAGE COUNTY LINE ON THIS ROAD SURVEY, AND THAT "THE CORRECTION FOR THE ROAD STONE WILL BE **10 FEET SOUTH**".

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 168 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 258 TO 260 PETITIONED BY WILLIAM CALDWELL AND OTHERS FOR TWO ROADS IN TOWNSHIP 18-13 [PACKET 473 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 18 & 19, 1882, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON JULY 14, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 21, 1882 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE GOVERNMENT STONE "IN PLACE"** AT THE NORTHEAST CORNER OF SECTION 22-18-13 ON THE LYON AND OSAGE COUNTY LINE FOR THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECOND ROAD EXTENDS WEST ON THE SECTION LINES FOR 3 MILES TO THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-18-13; THEN CONTINUES WEST ON THE SECTION LINES FOR 2,720 FEET TO THE STONE THAT HE FOUND ON THE BOUNDARY OF THE SAC & FOX LANDS; THEN CONTINUES WEST ON THE SECTION LINE FOR 2,420 FEET TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-18-13 ON THE RANGE LINE TO COMMENCE THIS SECOND ROAD ON THIS ROAD SURVEY
- 4) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 72 DATED NOVEMBER 7, 1883 FOR A ROAD IN TOWNSHIP 18, RANGE 13 FOR W. SOUTHWORTH, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 22-18-13 ON THE LYON AND OSAGE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS 60 FOOT WIDE ROAD EXTENDS NORTH ON THE COUNTY LINE TO THE STONE THAT HE SET AT 13.41 CHAINS NORTH OF THE EAST 1/4 CORNER OF SECTION 15-18-13; THEN CONTINUES NORTH ON THE COUNTY LINE AS AN 80 FOOT WIDE ROAD FOR 11.00 CHAINS TO THE STONE THAT HE SET AT 24.41 CHAINS NORTH OF THE EAST 1/4 CORNER OF SECTION 15-18-13; THEN CONTINUES NORTH ON THE COUNTY LINE AT 60 FEET WIDE TO THE STONE

THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 15-18-13 TO BEGIN THIS ROAD SURVEY

- 2) THIS 60 FOOT WIDE ROAD CONTINUES SOUTH ON THE COUNTY LINE TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-18-13 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY
  
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY ARTHUR E. MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 255 IN RECORDED ROAD RECORD BOOK "B" ON PAGES 606 TO 608 PETITIONED BY WILLIAM SOUTHWORTH AND OTHERS FOR A COUNTY ROAD ON THE LYON AND OSAGE COUNTY LINE IN TOWNSHIP 18-13 [PACKET 486 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 7, 1883, WAS ESTABLISHED AS 60 FOOT WIDE ROAD, **EXCEPT** AS SPECIFIED IN THE FIELD NOTES, ON JANUARY 10, 1884, AS NOTED BY J. E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON FEBRUARY 4, 1884 BY ROLAND LARKIN, COUNTY CLERK, APPARENTLY **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 22-18-13 ON THE LYON AND OSAGE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS 60 FOOT WIDE ROAD EXTENDS NORTH ON THE COUNTY LINE TO THE STONE THAT HE SET AT 13.41 CHAINS NORTH OF THE EAST 1/4 CORNER OF SECTION 15-18-13; THEN CONTINUES NORTH ON THE COUNTY LINE AS AN 80 FOOT WIDE ROAD FOR 11.00 CHAINS TO THE STONE THAT HE SET AT 24.41 CHAINS NORTH OF THE EAST 1/4 CORNER OF SECTION 15-18-13; THEN CONTINUES NORTH ON THE COUNTY LINE AT 60 FEET WIDE TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 15-18-13 TO BEGIN THIS ROAD SURVEY
  - 2) THIS 60 FOOT WIDE ROAD CONTINUES SOUTH ON THE COUNTY LINE TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-18-13 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY
  
- 6) STEVEN S. BROSEMER, L.S. 752, IN SURVEY F23001 IN THE SURVEY FILE FOR TOWNSHIP 18-13, DATED MARCH 18, 1982 ON FILE IN THE COUNTY ENGINEER'S OFFICE FOR THE SURVEY OF A 45 ACRE TRACT IN THE NORTHWEST QUARTER OF SECTION 23-18-13 IN OSAGE COUNTY, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTHWEST CORNER OF SECTION 23-18-13 ON THE LYON AND OSAGE COUNTY LINE WITH A COUNTY MAINTAINER, BUT HE DID **NOT** FIND THE STONE. HE FOUND A #4 REBAR OF UNKNOWN ORIGIN BUT IT WAS **NOT** ACCEPTED. HE CONSIDERED THAT THIS CORNER WAS OBLITERATED. **HE SET A #4 X 24" REBAR WITH HIS "BROSEMER LS 752" CAP** FOR THE NORTHWEST CORNER OF SECTION 23-18-13 ON THE LYON AND OSAGE COUNTY LINE BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER, I.E., THE FENCES WERE FOUND TO BE IN A REASONABLE POSITION FOR THIS LOCATION FOR THIS CORNER.
  - 1) 37.0' NE TO A SPIKE & WASHER IN A CORNER FENCE POST
  - 2) 56.8' SE TO A SPIKE & WASHER IN A BRACE POST
  - 3) 28.5' WEST TO A SPIKE & WASHER IN A CORNER FENCE POST
  - 4) 28.0' EAST AND WEST TO A LINE OF FENCE TO THE NORTH
  - 5) 24.0' NORTH AND SOUTH TO A LINE OF FENCE TO THE EAST
  - 6) 2.0' SOUTH TO A LINE OF FENCE TO THE WEST
  - 7) **2.5' NORTH TO A FOUND #4 REBAR OF UNKNOWN ORIGIN**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,354.65' SOUTH ON THE COUNTY LINE TO THE SOUTHEAST CORNER OF THE 45 ACRE TRACT
  - 2) 2,644.30' SOUTH ON THE COUNTY LINE TO THE #4 REBAR WITH HIS "BROSEMER LS 752" CAP THAT HE SET FOR THE WEST 1/4 CORNER OF SECTION 23-18-13

HIS INFORMATION IS CONTINUED ON PAGE 3

- 3) 5,288.60' SOUTH ON THE COUNTY LINE TO THE #4 REBAR WITH HIS "BROSEMER LS 752" CAP THAT HE SET FOR THE SOUTHWEST CORNER OF SECTION 23-18-11

NORTHEAST CORNER 22-18-13