

**NORTH 1/4 CORNER SECTION 29, TOWNSHIP 18 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 645 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 8" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-18-13 ON OCTOBER 20, 1856. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.15 CHAINS WEST TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-18-13
  - 2) 40.15 CHAINS EAST TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-18-13
  
- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 147 AT THE REQUEST OF B. F. PRICE OF READING, KANSAS TO LOCATE THE SOUTH LINE OF SECTION 29-18-13 AND EAST LINES OF SECTIONS 20 AND 29-18-13, SAID THAT HE DID **NOT** FIND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 20-18-13 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 20-18-13 EAST TO THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 27-18-13. HE DID **NOT** RESET THE SOUTH 1/4 CORNER OF SECTION 20-18-13 ON THIS **INFORMAL SURVEY**.
  
- 3) STEVEN S. BROSEMER, P.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 20, 2016 FOR PROJECT NUMBER 16131-02, THE SURVEY OF A PROPOSED ROAD VACATION ON THE NORTH LINE OF SECTIONS 29 AND 30, TOWNSHIP 18, RANGE 13 FOR THE LYON COUNTY ROAD AND BRIDGE DEPARTMENT, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 18-13, SAID THAT **HE FOUND AN EXISTING 1" IRON PIN PROTRUDING 2" OF "UNCERTAIN ORIGIN" BUT IN A VERY REASONABLE POSITION** AT THE SOUTH 1/4 CORNER OF SECTION 20-18-13. HE COMMENTED THAT IT COULD HAVE BEEN BY COUNTY ENGINEER E. C. GOLDSMITH OR LATER BY COUNTY SURVEYOR L. M. GOULD.
  - 1) THIS 1" IRON PIN IS ON THE EAST SIDE OF A LINE OF FENCE NORTH-SOUTH
  - 2) 25.6' SSE TO A CONCRETE NAIL & BOTTLECAP SET IN A BRACE POST
  - 3) 24.6' SOUTH TO A CONCRETE NAIL & BOTTLECAP SET IN THE EAST SIDE OF A CORNER FENCE POST
  - 4) 24.2' NORTH TO A CONCRETE NAIL & BOTTLECAP SET IN THE EAST SIDE OF A CORNER FENCE POST
  - 5) 25' SOUTH TO A LINE OF FENCE TO THE EAST
  - 6) 24.7' NORTH TO A LINE OF FENCE TO THE WEST
  - 7) TRUE STATE PLANE COORDINATES:  
NORTHING = 1976106.137      EASTING = 2029126.613HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,658.56' EAST TO THE 3/4" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 20-18-13 FROM THE GOLDSMITH INFORMAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 147
  - 2) 2,659.73' WEST TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 20-18-13. 2' EAST TO A LINE OF FENCE NORTH-SOUTH, 29' SOUTH TO A PIPE CORNER POST, AND 16' NORTH TO A HEDGE CORNER POST
  - 3) 5,306.53' WEST TO THE 5/8" X 25" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 19-18-13
  - 4) 5,544.73' WEST TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET AT THE INTERSECTION OF THE WEST BOUNDARY OF THE SAC & FOX TRUST LANDS WITH THE SOUTH LINE OF THE SW1/4 OF SECTION 19-18-13
  - 5) 7,902.90' WEST TO THE 1/2" REBAR WITH "PS 1168" CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 30-18-13 ON THE RANGE LINE

NORTH QUARTER CORNER 29-18-13