

WEST 1/4 CORNER SECTION 30, TOWNSHIP 18 SOUTH, RANGE 13 EAST

- 1) ON PAGE 91 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 11" X 3"** FOR THE WEST 1/4 CORNER OF SECTION 30-18-13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 27, 1855.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 26" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-18-13
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 21" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-18-13

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 113 RECORDED IN SURVEY BOOK "A" ON PAGES 203 & 204 DATED MAY 11, 1869 FOR A SURVEY OF SECTIONS 25 & 26-18-12, TO SURVEY THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 26, AND THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 26, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 25-18-12 ON THE RANGE LINE ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 235 RODS WEST TO THE STONE HE SET FOR THE SOUTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 25-18-12
 - 2) 315 RODS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 25-18-12

WEST QUARTER CORNER SECTION 30-18-13