

**NORTH 1/4 CORNER SECTION 34, TOWNSHIP 18 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 636 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 15" X 3-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-18-13.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS WEST TO THE 18" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-18-13
  - 2) 40.00 CHAINS EAST TO THE 20" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-18-13 ON THE COUNTY LINE
  
- 2) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 24, 1983, SAID THAT **HE FOUND A 3" X 10" X 15" LIMESTONE WITH THE LONG AXIS EAST-WEST OF UNCERTAIN ORIGIN** AT THE NORTH 1/4 CORNER OF SECTION 34-81-13, BUT IN A REASONABLE POSITION. **HE DROVE A 5/8" REBAR ON THE NORTH AND SOUTH SIDES OF THE STONE AND AT THE CENTER OF THE STONE.**
  - 1) 23.3' SOUTH TO A LINE OF FENCE TO THE WEST
  - 2) 30.5' SOUTH TO A LINE OF HEDGE TO THE EAST
  - 3) 23.0' NORTH TO A LINE OF FENCE TO THE WEST
  - 4) 4.0' EAST TO A LINE OF HEDGE TO THE SOUTH [EXTENDED]
  - 5) 4.0' EAST TO A LINE OF FENCE TO THE NORTH [EXTENDED]
  - 6) 2.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD

NORTH QUARTER CORNER 34-18-13