

**NORTH 1/4 CORNER SECTION 01, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 47 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 11" X 3"** FOR THE NORTH 1/4 CORNER OF SECTION 1-19-10 ON THE TOWNSHIP LINE ON NOVEMBER 27, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 23" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-19-10
- 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 24" X 24" X 2" LIMESTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 18 & 19 SOUTH, RANGES 10 & 11 EAST AT THE NORTHEAST CORNER OF SEC. 1-19-10

- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F01004 IN THE SURVEY FILE FOR TOWNSHIP 19-10 SHOWING THE LINES AND CORNERS OF THE EAST HALF OF THE NORTHEAST QUARTER OF SECTION 1-19-10 DATED APRIL 25, 1972 SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 1-19-10 ON THE TOWNSHIP LINE. THERE ARE NO TIES ON THE SURVEY OR IN THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.35' EAST ON THE TOWNSHIP LINE TO THE IRON PIN AT THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 1-19-10
- 2) 2,638.7' EAST ON THE TOWNSHIP LINE TO THE IRON PIN AT THE NORTHEAST CORNER OF SECTION 1-19-10 AT THE TOWNSHIP CORNER
- 3) 2,626' SOUTH TO THE CENTER CORNER OF SECTION 1-19-10—NOT IDENTIFIED

- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F36006 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 36 DATED DECEMBER 5, 1975, HE SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE SOUTH 1/4 OF SECTION 36-18-10 ON THE TOWNSHIP LINE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.8' WEST ON THE TOWNSHIP LINE TO THE STONE IN PLACE HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 36-18-10 THAT WAS USED BY RUGGLES IN 1916
- 2) 1,319.8' EAST ON THE TOWNSHIP LINE TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 36-18-10

- 4) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 17, 2001, FOR PROJECT NUMBER 01340-02, SURVEY F36009 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF TWO TRACTS IN THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 36-18-10, SAID THAT SHE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 36-18-10 ON THE TOWNSHIP LINE. **SHE FOUND THE GLO STONE** AT THIS CORNER. **SHE PLACED A 5/8" REBAR WITH A LYON COUNTY CAP BENT OVER THE TOP CENTER OF THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 36-18-10 ON THE TOWNSHIP LINE.

- 1) 30.35' SW TO A MASONRY NAIL & BOTTLE CAP IN THE WEST GATE POST
- 2) 30.60' SOUTH TO THE NORTH FACE OF A PIPE FENCE CORNER POST
- 3) 36.20' SE TO THE NEAR FACE OF A PIPE GATE POST
- 4) **1.81' SOUTH & 1.46' WEST OF A PRIOR MONUMENT – A 1/2" REBAR OF UNCERTAIN ORIGIN**
- 5) IN LINE WITH A FENCE TO THE SOUTH
- 6) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 190

HER INFORMATION IS CONTINUED ON PAGE 2

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,317.87' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 36-18-10 [ATTRIBUTABLE TO MILES, L.S. 667]
  - 2) 2,637.05' WEST ON THE TOWNSHIP LINE TO THE 1/2" SQUARE REBAR SHE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 36-18-10
  - 3) 2,639.40' EAST ON THE TOWNSHIP LINE TO THE 1/2" BOLT IN ASPHALT SHE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 36-18-10
  - 4) 2,645.91' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 36-18-10
  - 5) 3,967.27' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 36-18-10
  - 6) 5,288.63' NORTH TO THE STONE SHE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 36-18-10 WITH 5/8" REBARS WITH LYON COUNTY CAPS ON THE NORTH & SOUTH SIDES OF THE STONE
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 25, 2001, FOR PROJECT NUMBER 01414-02, SAID THAT **HE FOUND THE GLO STONE WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP ON THE SOUTH SIDE OF THE STONE ANGLED AND OVER THE TOP OF THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 1-19-10 ON THE TOWNSHIP LINE FROM THE EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, L.S. 1130, DATED OCTOBER 2001.
- 1) 30.6' SOUTH TO THE NEAR FACE OF A PIPE FENCE POST
  - 2) 30.35' SW TO A CONCRETE NAIL & WASHER IN A FENCE POST
  - 3) 36.2' SE TO THE NEAR FACE OF A PIPE GATE POST
  - 4) IN LINE WITH A FENCE TO THE SOUTH
  - 5) 1/2" X 24" REBAR WITH CAP WAS SET UNDER THE STONE
  - 6) THE TOP OF STONE IS 6" DEEP; THE TOP OF THE 5/8" REBAR IS 3" DEEP
  - 7) **2.3' NE TO A 1/2" REBAR FOUND**
- HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) 2,619.19' SOUTH TO THE CENTER CORNER OF SECTION 1-10-19
  - 2) 5,260.11' SOUTH TO THE SOUTH 1/4 CORNER OF SECTION 1-19-10

NORTH QUARTER CORNER 01-19-10