

NORTHWEST CORNER SECTION 01, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 47 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 10" X 3"** FOR THE CORNER TO SECTIONS 1 & 2-19-10 ON THE TOWNSHIP LINE.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 19" X 11" X 3" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 1-19-10
 - 2) 80.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 24" X 24" X 2" LIMESTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 18 & 19 SOUTH, RANGES 10 & 11 EAST AT THE NORTHEAST CORNER OF SEC. 1-19-10
 - 3) 39.75 CHAINS SOUTH TO THE 16" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 1 & 2-19-10
 - 4) 79.75 CHAINS SOUTH TO THE 26" X 5" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-19-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 26 TO 28 FOR ROAD NUMBER 7 BY A PETITION BY JOHN PATTY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 18-10 AND 19-10 [PACKET 104 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 26, 1878, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 7, 1878, AND WAS RECORDED ON NOVEMBER 7, 1878 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 1-19-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHWEST CORNER OF SECTION 36-18-10; THEN CONTINUES EAST ON THE SECTION LINES FOR 2,640' TO THE 1/4 SECTION CORNER ON THE NORTH LINE OF SECTION 36-18-10 TO THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 12-19-10 TO COMMENCE THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 159 DATED SEPTEMBER 4, 1878, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 1-19-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCE:
 - 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR TWO MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 12-19-10 AT THE BEGINNING OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR ONE MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-18-10

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGES 254 AND 255 FOR ROAD NUMBER 167 BY A PETITION BY W. R. GRIFFITH [PACKET 416 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED MAY 1882, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 2-19-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.

- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 5 FOR A ROAD SURVEY BETWEEN TOWNSHIPS 18-10 AND 19-10 DATED MAY 23, 1882, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 1-19-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 79.76 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF TOWNSHIP 19-10 TO BEGIN THIS ROAD SURVEY
 - 2) 80.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 2-19-10
 - 3) 79.80 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 3-19-10
 - 4) 159.77 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 4-19-10 AT THE TERMINUS OF THIS ROAD SURVEY
 - 5) THE WIDTH OF THE ROAD IS 50 FEET FROM THE BEGINNING TO A RAVINE AT 19.10 CHAINS WEST OF THE NORTHEAST CORNER OF SECTION 2-19-10, WHERE THE WIDTH INCREASED TO 75 FEET – 25 FEET NORTH OF THE TOWNSHIP LINE AND 50 FEET SOUTH OF THE TOWNSHIP LINE – FOR A DISTANCE OF 4.45 CHAINS, WHERE THE WIDTH DECREASES TO 50 FEET FOR THE REMAINDER OF THE ROAD AS SURVEYED
- 6) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 167 RECORDED IN ROAD RECORD BOOK “B” ON PAGES 254 TO 256 PETITIONED BY WILLIAM F. GRIFFITH AND OTHERS FOR A COUNTY ROAD ON THE TOWNSHIP LINE BETWEEN TOWNSHIPS 18-10 AND 19-10 [PACKET 416 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON MAY 23, 1882, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, **EXCEPT** AS NOTED IN HIS SURVEY NOTES, ON JULY 14, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 21, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 2-19-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS 50 FOOT WIDE ROAD EXTENDS EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE NORTHEAST CORNER OF TOWNSHIP 19-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS 50 FOOT WIDE ROAD EXTENDS WEST ON THE TOWNSHIP LINE FOR 19.10 CHAINS AT A RAVINE WHERE THE WIDTH INCREASES TO 75 FEET – 25 FEET ON THE NORTH SIDE OF THE TOWNSHIP LINE AND 50 FEET ON THE TOWNSHIP LINE – TO A POINT 23.55 CHAINS WEST OF THE NORTHEAST CORNER OF SECTION 2-29-10, WHERE IT RETURNS TO THE TOWNSHIP LINE AND CONTINUES AS A 50 FOOT WIDE ROAD TO THE NORTHWEST CORNER OF SECTION 4-19-10 AT THE TERMINUS OF THIS ROAD SURVEY
- 7) LARGE SURVEY SR #01003 IN THE SURVEY DRAWER FOR TOWNSHIP 19-10 SHOWS A **“TEMPORARY POINT SET BY TRANSIT”** AT THE NORTHWEST CORNER OF SECTION 1-19-10 ON THE TOWNSHIP LINE. THERE IS NO NAME OR DATE ON THE SURVEY, BUT A PENCIL NOTE FOR THE NORTHWEST CORNER OF SECTION 6-19-11 SHOWS **“IRON PIN SET 8/9/56”** THAT WAS APPARENTLY SET ON LINE BETWEEN THE STONE THAT THEY FOUND AT THE NORTHWEST CORNER OF SECTION 2-19-10 AND THE STONE THAT THEY FOUND AT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 1-19-10.

THE SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,256.6’ SOUTH TO THE IRON PIN AT THE SOUTHWEST CORNER OF SEC. 1-19-10
- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS AN **IRON PIN** AT THE “NE CORNER SECTION 02-19-10” ON THE TOWNSHIP LINE.
- 1) 31.7’ NW TO THE BASE OF A CORNER FENCE POST
 - 2) 38.4’ SE TOA THE BASE OF A CORNER FENCE POST
 - 3) 34.3’ SW TOA THE BASE OF A CORNER FENCE POST

- 9) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 8, 1985, SURVEY F02001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE EAST 660 FEET OF THE SOUTH 660 FEET OF THE NORTHWEST QUARTER OF SECTION 1-19-10 RECORDED IN VOLUME 413 ON PAGE 875 AT THE REGISTER OF DEEDS OFFICE ON MARCH 15, 1985, SAID THAT **HE FOUND A 1/2" SQUARE REBAR ATTRIBUTABLE TO AI CHAMNESS** AT THE NORTHEAST CORNER OF SECTION 2-19-10 ON THE TOWNSHIP LINE.
- 1) 25.5' EAST TO A LINE OF FENCE TO THE NORTH-EXTENDED
 - 2) 24.5' NORTH TO A LINE OF FENCE TO THE NORTH-EXTENDED
 - 3) 31.8' SW TO A SPIKE & WASHER IN A DEADMAN
 - 4) 2.0' SOUTH AND 2.0' EAST TO THE TRAVELED WAY OF THE ROADS
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,631.6' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 2-19-10
 - 2) 5,272.2' WEST ON THE TOWNSHIP LINE TO THE GLO STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 2-19-10
 - 3) 2,613.60' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 2-19-10
 - 4) 5,253.40' SOUTH TO THE 1/2" SQUARE REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 2-19-10, ATTRIBUTABLE TO AI CHAMNESS
- 10) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 6, 1996, FOR PROJECT NUMBER 95024-02, THE GPS SURVEY OF EMPORIA AND LOCAL AREA, SAID THAT **SHE FOUND THE 1/2" SQUARE REBAR AT 1" BELOW THE GRAVEL ROAD SURFACE** AT THE NORTHWEST CORNER OF SECTION 1-19-10 ON THE TOWNSHIP LINE FROM TIES OF RECORD BY STEVEN S. BROSEMER, L.S. 752, DATED MARCH 1985.
- 1) 31.5' SW TO A SPIKE & WASHER IN THE SIDE OF A POWER POLE
 - 2) 32.4' NW TO A SPIKE & WASHER IN THE SIDE OF A POWER POLE
 - 3) 27.4' SE TO THE CENTERLINE OF THE END OF A CORRUGATED METAL PIPE CULVERT
 - 4) 59.8' ENE TO THE NEAR FACE OF A WILLIAMS GAS LINE MARKER POST
 - 5) 62.3' ESE TO THE NEAR FACE OF A WILLIAMS GAS LINE MARKER POST
 - 6) 3.0' EAST TO THE TRAVELED WAY OF COUNTY ROAD "F" NORTH-SOUTH
 - 7) STATE PLANE COORDINATES IN U.S. FEET AT GROUND LEVEL
NORTH = 1963585.624 EAST = 1953198.845
- 11) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 17, 2001, FOR PROJECT NUMBER 01340-02, SURVEY F36009 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF TWO TRACTS IN THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 36-18-10, SAID THAT **SHE FOUND THE 1/2" SQUARE REBAR** AT THE SOUTHWEST CORNER OF SECTION 36-18-10 ON THE TOWNSHIP LINE FROM HER 1996 REFERENCE TIES OF RECORD.
- 1) 3.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "F" NORTH-SOUTH
 - 2) 31.5' SW TO A SPIKE & WASHER IN A POWER POLE
 - 3) 34.4' NW TO A SPIKE & WASHER IN A POWER POLE
 - 4) 27.4' SE TO THE CENTER OF THE END OF A CORRUGATED METAL PIPE CULVERT
 - 5) 59.8' ENE TO THE NEAR FACE OF A WILLIAMS GAS LINE MARKER POST @ GROUND LEVEL
 - 6) 62.3' ESE TO THE NEAR FACE OF A WILLIAMS GAS LINE MARKER POST @ GROUND LEVEL
 - 7) 42.0' WNW TO A CAST IRON WATER VALVE [SOUTH MOST OF 4 VALVES]
- HER TIES ARE CONTINUED ON PAGE 4

8) 48.25' NNW TO A CAST IRON WATER VALVE [EAST MOST OF 4 VALVES]

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,300.19' NORTH TO THE 1/2" REBAR BENT OVER THE STONE SHE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF THE NW1/4 OF SECTION 36-18-10
- 2) 1,319.18' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 36-18-10 [ATTRIBUTABLE TO MILES, L.S. 667]
- 3) 2,637.05' EAST ON THE TOWNSHIP LINE TO THE GLO STONE SHE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 36-18-10, WITH A 5/8" REBAR WITH A LYON COUNTY CAP BENT OVER THE TOP CENTER OF THE STONE
- 4) 5,276.45' EAST ON THE TOWNSHIP LINE TO THE 1/2" BOLT IN ASPHALT SHE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 36-18-10

12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 11, 2006, FOR PROJECT NUMBER 06014-02, SURVEY F02006 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR THE SURVEY OF A 10.0 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 2-19-10 FOR BOBBY DOUDICAN, SAID THAT **HE FOUND THE 1/2" SQUARE REBAR** AT THE NORTHEAST CORNER OF SECTION 2-19-10 ON THE TOWNSHIP LINE FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, LS 1130, IN 2001, FOR PROJECT NUMBER 01340-02.

- 1) 36.5' SW TO A SPIKE IN THE TOP OF A CORNER FENCE POST
- 2) 59.9' ENE TO THE NEAR FACE OF A WILLIAMS GAS LINE MARKER POST AT GROUND LEVEL
- 3) 62.5' ESE TO THE NEAR FACE OF A WILLIAMS GAS LINE MARKER POST AT GROUND LEVEL
- 4) 42.0' WNW TO A CAST IRON WATER VALVE [SOUTH VALVE OF 4 VALVES]
- 5) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 190 EAST-WEST
- 6) 3.0' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "F" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 660.00' WEST ON THE TOWNSHIP LINE TO THE NORTHWEST CORNER OF THE 10.0 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25.00' SOUTH
- 2) 2,636.12' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 2-19-10
- 3) 660.00' SOUTH TO THE SOUTHEAST CORNER OF THE 10.0 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20.00' WEST
- 4) 2,613.51' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 2-18-10

13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 29, 2009, FOR PROJECT NUMBER 09115-02, SURVEY F02010 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A 9.69 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 2-19-10, SAID THAT **HE FOUND THE 1/2" SQUARE REBAR** AT THE NORTHEAST CORNER OF SECTION 2-19-10 ON THE TOWNSHIP LINE FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.

- 1) 36.50' SW TO A SPIKE IN THE TOP OF A CORNER FENCE POST
- 2) 59.90' ENE TO THE NEAR FACE OF A WILLIAMS GAS LINE MARKER POST AT GROUND LEVEL

HIS TIES ARE CONTINUED ON PAGE 5

- 3) 62.50' ESE TO THE NEAR FACE OF A WILLIAMS GAS LINE MARKER POST AT GROUND LEVEL
- 4) 23.10' SW TO THE TOP CENTER OF THE SOUTH END OF A DRAINAGE CULVERT PIPE
- 5) 32.45' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 6) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 190 EAST-WEST
- 7) 3.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "F" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,636.11' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 2-18-10
 - 2) 660.00' SOUTH TO THE NORTHEAST CORNER OF THE 9.69 ACRE TRACT AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT 20' WEST
 - 3) 1,298.54' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 2-18-10, BEING THE SOUTHEAST CORNER OF GOVERNMENT LOT 1 IN THE NE1/4 OF SECTION 2-19-10
 - 4) 2,613.51' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 2-19-10
- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 30, 2010 FOR PROJECT NUMBER 10163-02, SURVEY F35005 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A TRACT IN THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 35-18-10 FOR JOHN NEWLAND, SAID THAT **HE FOUND THE 1/2" SQUARE IRON PIN** AT THE SOUTHEAST CORNER OF SECTION 35-18-10 ON THE TOWNSHIP LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 3.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "F" NORTH-SOUTH
 - 2) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 190 EAST-WEST
 - 3) 36.60' SW TO A SPIKE IN THE TOP OF A CORNER FENCE POST
 - 4) 23.15' SW TO THE TOP CENTER OF AN 18" IRON PIPE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,650.54' NORTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 35-18-10 THAT WAS SET BY ALVA J. SMITH IN 1903
 - 2) 3,975.44' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 35-18-10
 - 3) 5,300.34' NORTH TO THE 1/2" REBAR OVER THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 35-18-10
 - 4) 2,636.03' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 35-18-10
 - 5) 5,272.15' WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 35-18-10

NORTHWEST CORNER 01-19-10