

CENTER CORNER SECTION 04, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) GREGORY A. MILES, L.S. 667, IN A LAND SURVEY REFERENCE REPORT DATED MAY 11, 1983, SAID THAT **HE SET A 1/2" REBAR WITH HIS "LS 667" CAP** FOR THE CENTER CORNER OF SECTION 4-19-10 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS.
 - 1) 14.3' NNE TO A NAIL IN AN OLD HEDGE CORNER FENCE POST
 - 2) 8.15' NNW TO A NAIL IN A STEEL FENCE POST
 - 3) 14.24' SE TO A NAIL IN THE BOTTOM OF A TRIPLE HEDGE ROOT IN THE FENCE
 - 4) 12.4' EAST TO A NORTH-SOUTH FENCE LINE
 - 5) 4.0' NORTH TO AN EAST-WEST FENCE LINE
 - 6) 2,652.60' WEST TO THE WEST 1/4 CORNER OF SECTION 4-19-10
 - 7) 2,655.90' EAST TO THE EAST 1/4 CORNER OF SECTION 4-19-10
 - 8) 2,648.28' SOUTH TO THE SOUTH 1/4 CORNER OF SECTION 4-19-10
 - 9) 2,669.86' NORTH TO THE NORTH 1/4 CORNER OF SECTION 4-19-10

- 2) AARON C. DAVIS, L.S. 1368, IN A LAND SURVEY REFERENCE REPORT DATED MAY 25, 2012 FOR PROJECT NUMBER 12128-02, SURVEY F04005 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY TO MARK THE WEST LINE OF THE NORTH HALF OF THE SOUTHEAST QUARTER OF SECTION 4-19-10 FOR MELVIN HARTIG, SAID THAT **HE FOUND A 1/2" REBAR** AT THE CENTER CORNER OF SECTION 4-19-10 FROM EXISTING REFERENCE TIES ON FILE AT THE LYON COUNTY ENGINEER'S OFFICE. HE NOTED THAT THIS REAR WAS SET BY [GREGORY A.] MILES IN 1983.
 - 1) 4.0' NORTH TO A LINE OF FENCE RUNNING EAST AND WEST
 - 2) 12.0' EAST TO A LINE OF FENCE TO THE NORTH AND SOUTH
 - 3) 7.5' NE TO A 40 D NAIL IN THE TOP OF A STEEL FENCE POST
 - 4) 7.70' NW TO A 60 D ANIL IN THE TOP OF A STEEL FENCE POST
 - 5) 19.55' ENE TO THE TOP CENTER OF A 5" STEEL PIPE CORNER FENCE POST
 - 6) 21.20' SE TO A CONCRETE NAIL & WASHER IN A TRIPLE HEDGE TREE
 - 7) 1,323.88' SOUTH TO THE 1/2" REBAR WITH "LS 667" CAP HE FOUND AT THE SOUTHWEST CORNER OF THE N1/2 OF THE SE1/4 OF SEC. 4 [**HORIZONTAL TIE**]

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 22, 2014 FOR PROJECT NUMBER 14100-02, THE SURVEY OF A 5 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 4-19-10 FOR MELVIN HARTIG AND BRAD HARTIG, SURVEY F04006 IN THE SURVEY FILE FOR TOWNSHIP 19-10, SAID THAT THE CENTER CORNER OF SECTION 4-19-10 WAS RESET AFTER HE DID NOT FIND THE REBAR SET BY MILES BY A RETRACEMENT OF PRIOR SURVEYS. **HE SAID THAT HE SET A 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP** FOR THE CENTER CORNER OF SECTION 4-19-10.
 - 1) 0.5' WEST TO A LINE OF FENCE NORTH-SOUTH
 - 2) 11.6' EAST TO A 40 D NAIL & BOTTLECAP IN THE WEST FACE OF A 36" DIAMETER HEDGE TREE
 - 3) 13' EAST TO A LINE OF HEDGE NORTH-SOUTH
 - 4) 3.5' NORTH TO A LINE OF FENCE EAST-WEST
 - 5) **9.1' SOUTH TO A 1/2" IRON PIN FOUND**
 - 6) 1,324.20' SOUTH TO A 1/2" IRON PIN [WEST 1/16TH CORNER SW1/4 OF SEC. 4-19-10]
 - 7) 2,648.40' SOUTH TO AN ALUMINUM KDOT CAP [S1/4 CORNER SECTION 4-19-10]

HIS SURVEY DRAWING SHOWS THE FOLLOWING ADDITIONAL INFORMATION:

 - 1) 2,325.48' EAST TO THE 1/2" X 24" IRON PIN WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 5 ACRE TRACT
 - 2) 1,630.48' EAST TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE SET AT 25 FEET WEST OF THE NORTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 4-19-10 AS A **WITNESS CORNER**
 - 3) 2,655.48' EAST TO THE GLO STONE HE FOUND AT THE NORTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 4-19-10

CENTER CORNER SECTION 04-19-10