

**NORTH 1/4 CORNER SECTION 04, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 46 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 27" X 12" X 5"** FOR THE NORTH 1/4 CORNER OF SECTION 4-19-10 ON THE TOWNSHIP LINE ON NOVEMBER 27, 1856.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 23" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-19-10
  - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 22" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-19-10
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 52, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 233 DATED JULY 1, 1902 ORDERED BY JONATHAN B. PARKER TO SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST AND SOUTHEAST CORNERS OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 33-18-10 AND RUN SUCH LINES AS MAY BE NECESSARY TO COMPLETE THE WORK, SAID THAT THE SOUTH 1/4 CORNER OF SECTION 33-18-10 ON THE TOWNSHIP LINE IS "SAID TO BE IN BUT IS NOT IN SIGHT" ON THIS **PERMANENT SURVEY**. HE SAID THAT HE DID NOT DIG FOR THE STONE ON THIS SURVEY. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 88 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 152" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- 3) REA BOOK 31 ON PAGE 7 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 33-18-10 ON THE TOWNSHIP LINE AT 2,642 FEET WEST OF THE SOUTHWEST CORNER OF SECTION 34-18-10 AND IN THE CENTER OF THE GRAVEL ROAD BY E. D. STOUL'S GARDEN.
  - 1) 19' SOUTH TO A WITNESS PIN 1' NORTH OF A WIRE FENCE AT AN IRON POST
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-10 SHOWS A **REA PIN** AT THE "SW CORNER SE 1/4 SECTION 33-18-10" ON THE TOWNSHIP LINE.
  - 1) 19' SOUTH TO AN IRON PIN
- 5) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 18, 1983, SAID THAT **HE FOUND THE 5" X 9" GLO LIMESTONE AT 4" DEEP** AT THE NORTH 1/4 CORNER OF SECTION 4-19-10 ON THE TOWNSHIP LINE. **HE MADE A DRILL HOLE IN THE TOP OF THE STONE, AND HE SET 5/8" X 24" REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE.**
  - 1) 29.5' NW TO THE NEAR FACE OF A 24" DIAMETER PINE TREE
  - 2) 24.1' NW TO THE NEAR FACE OF A CORNER FENCE POST
  - 3) 16.9' NORTH TO A LINE OF FENCE EAST-WEST
  - 4) 21.3' SOUTH TO A LINE OF FENCE EAST-WEST
  - 5) 14.6' NNW TO THE NEAR FACE OF A 22" DIAMETER ELM TREE
  - 6) 2,638.12' WEST TO THE NORTHWEST CORNER OF SECTION 4
  - 7) 2,637.70' EAST TO THE NORTHEAST CORNER OF SECTION 4
- 6) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 20, 2001, **FOUND THE 5" X 9" GLO STONE WITH THE DRILL HOLE IN THE TOP WITH THE 5/8" REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE, WITH THE TOP OF THE STONE 4" DEEP** AT THE NORTH 1/4 CORNER OF SECTION 4-19-10 ON THE TOWNSHIP LINE FROM THE TIES OF STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN MARCH 1983.

- 1) 24.1' NW TO A FOUND NAIL & BOTTLE CAP IN A CORNER FENCE POST
  - 2) 18.4' NNW TO A FOUND NAIL & BOTTLE CAP IN A BRACE POST
  - 3) 22.3' SW TO A FOUND NAIL & BOTTLE CAP IN A CORNER FENCE POST
  - 4) 4.3' WEST TO A FENCE BEARING SOUTH
  - 5) 17.3' WEST TO A FENCE BEARING NORTH
  - 6) 2.0' SOUTH TO THE TRAVELED WAY OF COUNTY ROAD 190 EAST-WEST
- 7) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 06, 2001, FOR PROJECT NUMBER 01391-02, SURVEY F33002 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A 6.672 ACRE TRACT IN THE SOUTHWEST 1/4 OF SECTION 33-18-10 FOR GARLAND RICHARDSON, SAID THAT **SHE FOUND THE GLO STONE WITH THE DRILL HOLE IN THE TOP WITH THE 5/8" REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-18-10 ON THE TOWNSHIP LINE FROM THE TIES OF RECORD BY STEVEN S. BROSEMER, L.S. 752, DATED MARCH 1983 AND WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, DATED FEBRUARY 2001.
- 1) 30.0' WEST TO A 40 D NAIL & WASHER IN A PINE TREE
  - 2) 15.45' NNW TO A 40 D SPIKE AND WASHER FOUND IN AN ELM TREE
  - 3) 22.45' SSW TO A MASONRY NAIL & BOTTLE CAP IN A CORNER FENCE POST
  - 4) 3.3' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 190
  - 5) 3.8' WEST TO A FENCE LINE TO THE SOUTH, (EXTENDED NORTH)
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 498.50' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHWEST CORNER OF THE 6.672 ACRE TRACT
  - 2) 2,638.25' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 33-18-10
  - 3) 25' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET ON THE RIGHT-OF-WAY LINE
  - 4) 583.00' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHEAST CORNER OF THE 6.772 ACRE TRACT
  - 5) 5,330.06' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTH 1/4 CORNER OF SECTION 33-18-10
- 8) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 5, 2006, FOR PROJECT NUMBER 06-LA, STAKING COUNTY RIGHT-OF-WAY, **FOUND THE 5" X 9" GLO STONE WITH THE DRILL HOLE IN THE TOP ABOUT 4" BELOW THE SURFACE OF THE GRAVEL ROAD** AT THE NORTH 1/4 CORNER OF SECTION 4-19-10 ON THE TOWNSHIP LINE FROM MY EXISTING REFERENCE TIES DATED FEBRUARY 2001 AND THE TIES OF POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED NOVEMBER 2001 ON FILE AT THE COUNTY ENGINEER'S OFFICE. I FOUND THE 5/8" REBARS ON THE NORTH AND SOUTH SIDES OF THE STONE, BUT THE CAPS WERE MISSING, SO I PLACED NEW LYON COUNTY CAPS ON THE REBARS, AND I RE-MARKED THE DRILL HOLE IN THE TOP OF THE STONE.
- 1) 29.9' NW TO A FOUND 60 D NAIL & WASHER IN A 6" CIRCUMFERENCE PINE TREE
  - 2) 22.6' SSW TO A FOUND MASONRY NAIL & BOTTLECAP IN A CORNER FENCE POST
  - 3) 20.3' NORTH TO THE TOP CENTER OF A 3" PIPE POST FILLED WITH CONCRETE
  - 4) IN LINE WITH A FENCE BEARING NORTH
  - 5) 3.3' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 190 EAST-WEST
  - 6) 3.8' WEST TO A FENCE LINE TO THE SOUTH

CONTINUED ON PAGE 3

- 9) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 7, 2007 FOR PROJECT NUMBER 07-NK, STAKING COUNTY RIGHT-OF-WAY, **FOUND THE 5" X 9" GLO STONE WITH THE DRILL HOLE IN THE TOP WITH THE 5/8" REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 4-19-10 ON THE TOWNSHIP LINE FROM MY EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE FROM JUNE 2006.
- 1) 29.9' NW TO A FOUND 60 D NAIL & WASHER IN A 6" CIRCUMFERENCE PINE TREE
  - 2) 22.6' SSW TO A FOUND MASONRY NAIL & BOTTLECAP IN A CORNER FENCE POST
  - 3) 20.3' NORTH TO THE TOP CENTER OF A 3" PIPE POST FILLED WITH CONCRETE
  - 4) IN LINE WITH A FENCE BEARING NORTH
  - 5) 3.3' SOUTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 190 EAST-WEST
  - 6) 3.8' WEST TO A FENCE LINE TO THE SOUTH
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 22, 2013, FOR PROJECT NUMBER 13086, SURVEY F33003 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR THE SURVEY OF THE WEST HALF OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 33-18-10 FOR JESSE MILLER, SAID THAT **HE FOUND THE [5" X 9" GLO] STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-18-10 ON THE TOWNSHIP LINE FROM HIS EXISTING TIES OF RECORD IN THE COUNTY SURVEYORS OFFICE. HE NOTED THAT HE HAD FOUND THIS STONE IN 1983.
- 1) 5/8" IRON PINS WITH CAPS ARE ON THE NORTH AND SOUTH SIDE OF THE STONE
  - 2) 29.7' WNW TO A SPIKE & WASHER IN THE SOUTH FACE OF AN 18" EVERGREEN TREE
  - 3) 20' NORTH TO THE TOP CENTER OF A 3" PIPE CORNER FENCE POST
  - 4) IN LINE WITH A FENCE TO THE NORTH
  - 5) 4' WEST TO A FENCE TO THE SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,638.26' WEST ON THE TOWNSHIP LINE TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 33-18-10
  - 2) 2,637.75' EAST ON THE TOWNSHIP LINE TO THE 5/8" IRON PIN WITH A CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 33-18-10
  - 3) 2,667.67' NORTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 33-18-10
  - 4) 3,999.71' NORTH TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE W1/2 OF THE NW1/4 OF THE NE1/4 OF SECTION 33-18-10
  - 5) 5,331.75' NORTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 33-18-10

NORTH QUARTER CORNER SECTION 04-19-10