

CENTER CORNER SECTION 05, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 19, 1998, FOR JOB NUMBER 97429-02, SAID THAT **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE CENTER CORNER OF SECTION 5-19-10.
 - 1) 26.5' ENE TO A PK NAIL & WASHER IN A CORNER FENCE POST
 - 2) 29.80' SE TO THE TOP CENTER OF THE SOUTH END OF A STEEL PIPE IN AN ENTRANCE
 - 3) 1.3' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
 - 4) 3.0' NORTH TO A LINE OF FENCE TO THE EAST

- 2) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 03, 2003, FOR JOB NUMBER 03026-02, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE NORTH HALF OF THE SOUTH HALF OF THE NORTH HALF OF THE WEST HALF OF THE SOUTHEAST QUARTER OF SECTION 5-19-10, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE CENTER CORNER OF SECTION 5-19-10 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED JUNE 1998.
 - 1) 26.80' ENE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 29.80' SE TO THE TOP CENTER OF THE SOUTH END OF A STEEL DRAINAGE PIPE FOR AN ENTRANCE
 - 3) 17.20' EAST TO THE TOP CENTER OF THE NORTH END OF A STEEL DRAINAGE PIPE FOR AN ENTRANCE
 - 4) 20' WEST TO A LINE OF POWER POLES TO THE NORTH EXTENDED
 - 5) 2.3' EAST TO THE CENTERLINE TRAVELED WAY OF ROAD "B5"
 - 6) 5.3' NORTH TO A LINE OF FENCE TO THE EAST EXTENDED

THE SURVEY DRAWING SIGNED BY STEVEN S. BROSEMER, L.S. 752, SHOWS THE FOLLOWING INFORMATION:

 - 1) 1,322.54' EAST TO THE THEORETICAL POSITION FOR THE NORTH 1/16TH CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 5-19-10
 - 2) 2,645.08' EAST TO THE 1/2" REBAR WITH "MACON COMPANY" CAP HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 5-19-10
 - 3) 661.77' SOUTH TO THE COTTON GIN SPINDLE HE SET FOR THE NORTHWEST CORNER OF THE N1/2 OF THE S1/2 OF THE N1/2 OF THE W1/2 OF THE SE1/4 OF SECTION 5-19-10
 - 4) 929.65' SOUTH TO THE COTTON GIN SPINDLE HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE S1/2 OF THE N1/2 OF THE W1/2 OF THE SE1/4 OF SECTION 5-19-10
 - 5) 1,323.53' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 5-19-10
 - 6) 2,647.06' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 5-19-10

CENTER CORNER OF SECTION 05-19-10