

NORTH 1/4 CORNER SECTION 05, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 46 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 7"** FOR THE NORTH 1/4 CORNER OF SECTION 5-19-10 ON THE TOWNSHIP LINE ON NOVEMBER 27, 1856.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 28" X 8" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-19-10
 - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 23" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-19-10

- 2) E. B. KIRKENDALL, SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 4 & 5 [PACKET 910 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE "PLYMOUTH AND AMERICUS ROAD" SURVEYED AUGUST 11, 1858, AND RECORDED IN THE COMMISSIONER'S JOURNAL ON PAGE 24 ON AUGUST 30, 1858, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 5-19-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY. NO WIDTH IS RECORDED AND BY THE TERRITORIAL LAW IN EFFECT AT THE TIME THE ROAD WOULD BE 40 FEET WIDE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO THE SOUTH 1/4 CORNER OF SECTION 5-19-10 AT THE NORTHEAST CORNER OF THE TOWNSITE OF PLYMOUTH
 - 2) THIS ROAD EXTENDS NORTHEASTERLY ACCORDING TO THE SURVEY NOTES

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 121 RECORDED IN SURVEY BOOK "A" ON PAGE 209 DATED MAY 27 & 28, 1869 TO SURVEY THE SOUTHEAST 1/4 COF SECTION 32-18-10 AND TO ESTABLISH THE CENTER CORNER OF SECTION 32-18-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 32-18-10 ON THE TOWNSHIP LINE ON THIS SURVEY.
HIS SURVEY NOES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS, 9 LINKS NORTH TO THE STONE HE SET FOR THE WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 32-18-10
 - 2) 160 RODS, NORTH TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 32-18-10
 - 3) 79 RODS, 8 LINKS EAST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE SOUTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 32-18-10
 - 4) 158 RODS, 16 LINKS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 32-18-10

- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 136 RECORDED IN SURVEY BOOK "A" ON PAGE 218 AND DATED OCTOBER 1869, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 32-18-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.

- 5) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 140 & 141 [PACKET 263 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] ON A PETITION BY T. E. McMILLAN AND OTHERS FOR A CHANGE IN THE "PLYMOUTH TO AMERICUS ROAD" THAT WAS SURVEYED ON OCTOBER 24, 1869 AND ESTABLISHED AND RECORDED ON NOVEMBER 5, 1869 BY J. L. WILLIAMS, COUNTY CLERK, AT THE "WIDTH TO CONFORM TO THE OLD ROAD", SAID THAT HE COMMENCED THIS ROAD SURVEY AT THE 1/4 CORNER ON THE SOUTH BOUNDARY OF SECTION 32-18-10 ON THE TOWNSHIP LINE **AT A STONE SET IN THE GROUND**. SEE THE COMMISSIONERS JOURNAL ON PAGE 292.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE FOR 159 RODS TO A TURN TO THE NORTH AT OR NEAR THE SOUTHEAST CORNER OF SECTION 32-18-10

- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 167 DATED JUNE 27, 1879, FOR A COUNTY ROAD IN TOWNSHIPS 18-10 AND 19-10, APPARENTLY **FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 5-19-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 29-18-10
- 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO A POINT 7,813' SOUTH OF THE STONE HE FOUND AT THE 1/4 CORNER ON THE NORTH LINE OF SECTION 8-19-10 WITH DEVIATIONS DUE TO GROWING HEDGES

- 7) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 27 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 106 TO 108 PETITIONED BY C. C. LYNCH AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 18-10 AND 19-10 [PACKET 111 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 24, 1879, WAS ESTABLISHED AT A 40 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 5-19-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY. SEE THE SURVEY NOTES FOR LOCATIONS WHERE THE RIGHT-OF-WAY LINE CHANGED DUE TO HEDGE FENCES.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE NORTH 1/4 CORNER OF SECTION 29-18-10; THEN TURNS TO THE EAST ON THE SECTION LINES FOR 2,640 FEET TO THE NORTHEAST CORNER OF SECTION 29-18-10 AND THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO A POINT ON THE WEST LINE OF THE EAST 1/2 OF SECTION 17-19-10 ON THE NORTH BANK OF THE COTTONWOOD RIVER TO COMMENCE THIS ROAD SURVEY

- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 169, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 169 DATED MAY 27, 1887 ORDERED BY T. E. McMILLEN TO LOCATE THE CENTER CORNER OF SECTION 32-18-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 32-18-10 ON THE TOWNSHIP LINE. **HE SET A 4' LONG BY 1" DIAMETER GAS PIPE ON THE NORTH SIDE OF THE STONE ON THIS PERMANENT SURVEY.** THIS SURVEY IS RECORDED IN VOLUME 41 ON PAGE 295 AT THE REGISTER OF DEEDS OFFICE AND SURVEY F32002 IN THE SURVEY FILE FOR TOWNSHIP 18-10.

- 9) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 18, 1983, SAID THAT **HE FOUND THE GLO STONE WITH A 1/2" REBAR WITH A RED PLASTIC CAP STAMPED "BROSEMER LS 82" OVER THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 5-19-10 ON THE TOWNSHIP LINE THAT WAS FOUND BY JAMES H. BROSEMER, L.S. 82, IN 1979.

- 1) 18.5' SOUTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
- 2) 34.7' WEST TO A LINE OF FENCE TO THE NORTH [EXTENDED]
- 3) 33.0' NORTH TO A LINE OF POWER POLES EAST-WEST
- 4) 9.0' NORTH TO THE TRAVELED WAY OF THE ROAD TO THE EAST
- 5) 17.0' WEST TO THE TRAVELED WAY OF THE ROAD TO THE NORTH

HIS TIES ARE ON PAGE 3

- 6) IN THE TRAVELED WAY OF THE ROAD TO THE SOUTH
 - 7) IN LINE WITH A FENCE TO THE WEST [EXTENDED]
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 19, 1998, FOR JOB NUMBER 97429-02 TO SUBDIVIDE THE NORTHWEST 1/4 OF SECTION 05-19-10, SAID THAT **HE FOUND THE 1/2" REBAR WITH "J. H. BROSEMER" CAP OVER THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 5-19-10 ON THE TOWNSHIP LINE FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED MARCH 1983.
- 1) 25.30' WEST TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
 - 2) 43.90' NE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
 - 3) 31.10' SE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
 - 4) 8.9' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE EAST
 - 5) IN THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE SOUTH
- 11) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 7, 2007 FOR PROJECT NUMBER 07-NK, **FOUND THE 1/2" REBAR WITH A RED "J. H. BROSEMER LS 82" CAP OVER THE STONE OF RECORD** AT THE NORTH 1/4 CORNER OF SECTION 5-19-10 ON THE TOWNSHIP LINE FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED MARCH 1983 AND JUNE 1988.
- 1) 42.90' NE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
 - 2) 31.10' SE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
 - 3) 42.75' NW TO A MAG NAIL & WASHER IN THE NORTHEAST FACE OF A POWER POLE
 - 4) 29.80' WEST TO THE NEAR FACE OF A 4" STEEL PIPE CORNER POST AT GROUND LEVEL
 - 5) 1' SOUTH TO A FENCE TO THE WEST EXTENDED
 - 6) 9' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 190 TO THE EAST ONLY
 - 7) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "B5" TO THE SOUTH
- 12) JAMES A. BRULL, L.S. 1475, ASSISTANT COUNTY ENGINEER AND DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED DECEMBER 3, 2009 FOR PROJECT NUMBER MS05, SECTION CORNER RECOVERY, SAID THAT **HE FOUND THE 1/2" REBAR WITHOUT A CAP OVER THE STONE OF RECORD AT 0.5' BELOW THE ROAD SURFACE** AT THE NORTH 1/4 CORNER OF SECTION 5-19-10 ON THE TOWNSHIP LINE FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 42.90' NE TO A 40 D SPIKE & WASHER IN THE WEST FACE OF A CORNER FENCE POST
 - 2) 29.40' SE TO A 40 D SPIKE & WASHER IN THE NORTHWEST FACE OF A CORNER FENCE POST
 - 3) 29.75' WEST TO THE NEAR FACE OF A 4" STEEL PIPE CORNER FENCE POST AT THE GROUND
 - 4) 1' SOUTH OF A FENCE TO THE WEST-EXTENDED
 - 5) 10' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 190 TO THE EAST ONLY
 - 6) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "B5" TO THE SOUTH
 - 7) 14' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "B5" TO THE NORTH

NORTH QUARTER CORNER 05-19-10