

NORTHWEST CORNER SECTION 06, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 33 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 30" X 17" X 3" WITH A MOUND OF ROCKS** FOR THE CORNER TO TOWNSHIPS 18 & 19 SOUTH, RANGES 9 & 10 EAST ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE AT THE NORTHWEST CORNER OF SECTION 6-19-10 ON NOVEMBER 19, 1856.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION
 - 1) 39.90 CHAINS EAST ON THE TOWNSHIP LINE TO THE 30" X 6" X 3" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 6-19-10
 - 2) 79.90 CHAINS EAST ON THE TOWNSHIP LINE TO THE 28" X 8" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-19-10
 - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 26" X 13" X 2" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-19-10
 - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 21" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-19-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE BOTTOM RIGHT SIDE PAGE 165 DATED JUNE 18, 1879, FOR A COUNTY ROAD ON THE TOWNSHIP LINE BETWEEN TOWNSHIPS 19-10 AND 19-11, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 31-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 5,280' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-19-10
 - 2) 10,560' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 32-19-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) W. W. SANDERS, CHASE COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 211 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 430 & 431 PETITIONED BY WILLIAM FLICKENGER AND OTHERS FOR A ROAD ON THE CHASE/LYON COUNTY LINE [PACKET 474 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 15, 1883, AND WAS ESTABLISHED AS A 45 FOOT WIDE ROAD – 22-1/2 FEET EACH SIDE OF THE COUNTY LINE – BY THE LYON COUNTY BOARD OF COUNTY COMMISSIONERS ON APRIL 13, 1883 AS NOTED BY WILLIAM F. EWING, LYON COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 31-18-10 AT THE TOWNSHIP CORNER ON THE RANGE LINE AND THE CHASE AND LYON COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE COUNTY LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-19-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE COUNTY LINE FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-19-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 36 TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS OF THE SOUTHWEST AND THE SOUTHEAST QUARTERS OF SECTION 19-18-10 THAT BEGAN ON JANUARY 13, 1958 AND CARRIED ON AT INTERVALS, WITH SEVERAL POSTPONEMENTS UNTIL

COMPLETED, SAID THAT HE FOUND THE “APPARENT CORNER OF TOWNSHIP 18, RANGE 10, THE SOUTHWEST CORNER OF SECTION 31-18-10” ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE ON THIS PERMANENT SURVEY.

NOTE: VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS HE DOES NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THE “APPARENT CORNER” AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES – WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,287.6’ NORTH ON THE RANGE LINE AND COUNTY LINE TO THE COMPUTED LOCATION FOR THE NORTHWEST CORNER OF SECTION 31-18-10
 - 2) 10,575.2’ NORTH ON THE RANGE LINE AND COUNTY LINE TO THE IRON PIN HE DROVE FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 19-18-10
 - 3) 13,219.0’ NORTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 19-18-10
 - 4) 15,862.8’ NORTH ON THE RANGE LINE AND COUNTY LINE TO THE 3/4” DIAMETER IRON PIN HE DROVE FOR THE PERMANENT NORTHWEST CORNER OF SECTION 19-18-10
 - 5) 18,506.6’ NORTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 18-18-10
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 21, 2004, FOR PROJECT NUMBER 04169-02, SAID THAT HE CONSIDERED THAT THE NORTHEAST CORNER OF SECTION 1-19-9 ON THE RANGE LINE AND THE CHASE AND LYON COUNTY LINE WAS **OBLITERATED**. HE SET A 5/8” X 24” REBAR WITH A LYON COUNTY CAP IN THE CENTER OF THE NORTH-SOUTH [45’] ROAD AND IN LINE WITH A FENCE TO THE WEST FOR THE NORTHEAST CORNER OF SECTION 1-19-9 ON THE RANGE LINE AND THE COUNTY LINE.
- 1) **22.3’ WSW TO A 1/2” REBAR FOUND**
 - 2) 20.07’ WEST TO A CONCRETE NAIL & SHINER IN A FENCE BRACE POST
 - 3) 23.65’ WSW TO A CONCRETE NAIL & SHINER IN A CORNER GATE POST
 - 4) 22.35’ ENE TO A CONCRETE NAIL & SHINER IN A GATE POST
 - 5) 28.65’ NE TO A CONCRETE NAIL & WASHER IN A GATE POST
 - 6) IN THE CENTERLINE TRAVELED WAY OF GRAVEL LYON COUNTY ROAD “A” NORTH-SOUTH
 - 7) IN LINE WITH A FENCE TO THE WEST
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 21, 2009 FOR PROJECT NUMBER 09136-02, SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 TO SURVEY THE WEST LINE OF THE EAST HALF OF THE EAST HALF OF THE SOUTHWEST QUARTER OF SECTION 6-19-10 FOR PAUL HANCOCK, SAID THAT HE FOUND THE 5/8” REBAR WITH A LYON COUNTY CAP AT THE NORTHWEST CORNER OF SECTION 6-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED MAY 2004.
- 1) **22.3’ WSW TO A 1/2” REBAR FOUND**
 - 2) 20.7’ WEST TO A CONCRETE NAIL & SHINER IN A FENCE BRACE POST
 - 3) 23.65’ WSW TO A CONCRETE NAIL & SHINER IN A CORNER GATE POST
 - 4) 22.35’ ENE TO A CONCRETE NAIL & SHINER IN A GATE POST
 - 5) 28.65’ NE TO A CONCRETE NAIL & WASHER IN A GATE POST
 - 6) IN THE CENTERLINE TRAVELED WAY OF GRAVEL LYON COUNTY ROAD “A” NORTH-SOUTH
 - 7) IN LINE WITH A FENCE TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 3

- 1) 1,317.21' EAST ON THE TOWNSHIP LINE TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 6-19-10
- 2) 2,641.04' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 6-19-10
- 3) 5,280.80' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 6-19-10
- 4) 2,645.39' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-19-10
- 5) 5,290.49' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE 1/2" REBAR WITH AN ALUMINUM KDOT CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 6-19-10

NORTHWEST CORNER SECTION 06-19-10