

WEST 1/4 CORNER SECTION 06, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 33 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 26" X 13" X 2"** FOR THE WEST 1/4 CORNER OF SECTION 6-19-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE ON NOVEMBER 19, 1856.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY AND COUNTY LINE TO THE 30" X 17" X 3" LIMESTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 18 & 19 SOUTH, RANGES 9 & 10 EAST
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND COUNTY LINE TO THE 21" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-19-10

- 2) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **REA PIN** AT THE WEST 1/4 CORNER OF SECTION 6-19-10 ON THE RANGE LINE AND LYON AND CHASE COUNTY LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 17' EAST TO A WITNESS [REA]

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 21, 2004, FOR PROJECT NUMBER 04169-02, SAID THAT HE CONSIDERED THAT THE EAST 1/4 CORNER OF SECTION 1-19-9 ON THE RANGE LINE AND THE CHASE AND LYON COUNTY LINE WAS **LOST. HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 1-19-9 ON THE RANGE LINE AND THE CHASE AND LYON COUNTY LINE AT HALFWAY BETWEEN THE NORTHEAST CORNER AND THE SOUTHEAST CORNER OF SECTION 1-19-9.
 - 1) 22.5' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET
 - 2) 23.45' EAST TO A 40 D NAIL & WASHER IN A POWER POLE
 - 3) 21.6' WNW TO A CONCRETE NAIL & WASHER IN A GATE POST
 - 4) IN LINE WITH A FENCE TO THE WEST

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 21, 2009 FOR PROJECT NUMBER 09136-02, SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 TO SURVEY THE WEST LINE OF THE EAST HALF OF THE EAST HALF OF THE SOUTHWEST QUARTER OF SECTION 6-19-10 FOR PAUL HANCOCK, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4 CORNER OF SECTION 6-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED MAY 2004.
 - 1) 22.5' WEST TO A 1/2" REBAR WITH HIS CAP SET
 - 2) 23.45' EAST TO A 40 D NAIL & WASHER IN A POWER POLE
 - 3) 21.6' WNW TO A CONCRETE NAIL & BOTTLECAP IN A GATE POST
 - 4) 24.85' ENE TO A 3/8" BOLT ON THE SOUTH FACE OF A FENCE POST
 - 5) 25.8' WEST TO A CONCRETE NAIL & BOTTLECAP IN THE EAST FACE OF A CORNER FENCE POST
 - 5) IN LINE WITH A FENCE TO THE WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,645.10' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE 1/2" REBAR WITH AN ALUMINUM KDOT CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 6-19-10HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,645.39' NORTH ON THE RANGE LINE AND COUNTY LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 6-19-10 AT THE TOWNSHIP CORNER
- 3) 1,277.76' EAST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 6-19-10
- 4) 1,937.54' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE E1/2 OF THE SW1/4 OF SEC. 6-19-10
- 5) 2,597.32' EAST TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE E1/2 OF THE E1/2 OF THE SW1/4 OF SECTION 6-19-10
- 6) 5,235.59' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 6-19-10

WEST QUARTER CORNER SECTION 06-19-10