

WEST 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 07, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 101 RECORDED IN SURVEY BOOK "A" ON PAGE 194 DATED MARCH 18, 1869 FOR A SURVEY OF LAND IN SECTION 7-19-10, TO ESTABLISH THE 1/4 CORNER ON THE WESTERN BOUNDARY, ALSO THE CENTER CORNER, AND ALSO THE SUBDIVISIONAL CORNER ON THE WESTERN BOUNDARY OF THE NORTHEAST 1/4 OF SECTION 7, SAID THAT **HE SET A STONE** FOR THE 1/2/4 CORNER ON THE WESTERN BOUNDARY OF THE NORTHEAST 1/4 OF SECTION 7 EQUIDISTANT BETWEEN THE STONE HE SET FOR THE CENTER CORNER AND THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 7 ON THIS SURVEY.

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 6, 2003, FOR PROJECT NUMBER 03042-02, SAID THAT THE STONE SET BY D. T. McAULEY FROM SURVEY BOOK "A" ON PAGE 194 [DATED 1869] WAS SEARCHED FOR BUT WAS **NOT** FOUND. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE EAST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 7 ON TRUE LINE AND HALFWAY BETWEEN THE NORTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 7.
 - 1) IN LINE WITH A LINE OF HEDGE TO THE SOUTH
 - 2) 7.15' SOUTH TO A 40 D NAIL & WASHER IN THE ROOT OF A 16" ELM TREE
 - 3) 5.75' NW TO A 40 D NAIL & WASHER IN A 6" ELM TREE
 - 4) 12.25' NE TO A 40 D NAIL & WASHER IN A 24" ELM TREE
 - 5) 4.0' NORTH TO A LINE OF HEDGE TO THE EAST

WEST SIXTEENTH CORNER NORTHEAST QUARTER OF SECTION 07-19-10