

NORTH 1/16TH CORNER NORTHEAST QUARTER SECTION 08, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE NORTH HALF OF THE SOUTH HALF OF THE NORTH HALF OF THE WEST HALF OF THE SOUTHEAST QUARTER OF SECTION 5-19-10 FOR PROJECT NUMBER 03026-02 DATED FEBRUARY 7, 2003 SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 5-19-10 TO BE ON LINE AND HALFWAY BETWEEN THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 5-19-10, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,325.48' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 5-19-10
 - 2) 1,325.48' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 5-19-10
 - 3) 1,325.51' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 5-19-10
 - 4) 1,656.89' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE S1/2 OF THE N1/2 OF THE W1/2 OF THE SE1/4 OF SECTION 5-19-10
 - 5) 1,988.27' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE N1/2 OF THE S1/2 OF THE N1/2 OF THE W1/2 OF THE SE1/4 OF SECTION 5-19-10
 - 6) 2,651.03' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 5-19-10
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 17, 2007 FOR PROJECT NUMBER 07319-02, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE EAST HALF OF THE NORTHEAST QUARTER AND THE NORTH HALF OF THE NORTHWEST QUARTER OF THE NORTHEAST QUARTER OF SECTION 8-19-10 FOR MERT DEBOER, SAID THAT **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 8-19-10 ON TRUE LINE AND HALFWAY BETWEEN THE NORTH QUARTER CORNER AND THE NORTHEAST CORNER OF SECTION 8-19-10.

- 1) IN LINE WITH A HEDGE ROW TO THE NORTH
- 2) 2.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 180 EAST-WEST
- 3) 28.15' NNE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 4) 59.05' ENE TO A 40 D SPIKE & WASHER IN THE SOUTH FACE OF A POWER POLE
- 5) 25.0' SOUTH TO A 1/2" REBAR WITH HIS CAP SET

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,324.48' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 8-19-10
- 2) 1,324.48' EAST TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 8-19-10
- 3) 662.94' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE NW1/4 OF THE NE1/4 OF SEC. 8-19-10
- 4) 1,325.88' SOUTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF THE NE1/4 OF SECTION 8-19-10
- 5) 2,651.75' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 8-19-10

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 08-19-10

