

**NORTH 1/16TH CORNER SOUTHEAST QUARTER SECTION 08, TOWNSHIP 19 SOUTH,
RANGE 10 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 17, 2007 FOR PROJECT NUMBER 07319-02, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE EAST HALF OF THE NORTHEAST QUARTER AND THE NORTH HALF OF THE NORTHWEST QUARTER OF THE NORTHEAST QUARTER OF SECTION 8-19-10 FOR MERT DEBOER, SAID THAT THAT **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 8-19-10 ON TRUE LINE AND HALFWAY BETWEEN THE CENTER CORNER AND THE EAST QUARTER CORNER OF SECTION 8-19-10.

- 1) 4.5' SOUTH TO THE CENTERLINE TRAVELED WAY
- 2) 15.0' NORTH TO A 1/2" REBAR WITH HIS CAP SET
- 3) IN LINE WITH A HEDGE ROW TO THE NORTH
- 4) 20.5' NNW TO A SPIKE & WASHER IN A CORNER FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327.18' WEST TO THE 1/2" REBAR WITH A "GEOTECH" CAP HE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 8-19-10
- 2) 1,327.17' EAST TO THE 5/8" REBAR WITH A KDOT CAP HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 8-19-10
- 3) 1,325.87' NORTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF THE NE1/4 OF SECTION 8-19-10
- 4) 1,988.81' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE NW1/4 OF THE NE1/4 OF SEC. 8-19-10
- 5) 2,651.75' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/16TH CORNER OF THE NE1/4 OF SECTION 8-19-10

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 08-19-10